NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

WATER RESOURCES DEPARTMENT,
SALEM, OREGON 97310
Within 30 days from the date
of well completion.

STATE OF OREGON
(Please type or print)
(Do not write above this line)

WATER WELL REPORT

CLA	State Well No. 381W-27dd	
	State Well No.	Ĺ
08635	State Permit No.	

5-115-				
(1) OWNER: V. (752 201978	(10) LOCATION OF WELL:			
Name Chick 17 Dec Will Bery	County Clackamas Driller's well no	umber		
Address 94130 Sivily Ahams Perry Rd	SE 14 SE 14 Section 27 T. 38			W.M.
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivisi	on corne	r	
New Well Deepening □ Reconditioning □ Abandon □				
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL Completed on	11		
(3) TYPE OF WELL: (4) PROPOSED USE (check):	(11) WATER LEVEL: Completed w	73		44
Rotary Driven Domestic Industrial Municipal	Static level 49 ft. below land		D-4- /	- 11.
Cable	Artesian pressure lbs. per squar			<u> </u>
CASING INSTALLED: Threaded Welded	(12) WELL LOG: Diameter of well			
10 " Diam. from O ft. to1 9 2 ft. Gage .025	Depth drilled 192 ft. Depth of completed well 197 ft.			
" Diam. from ft. to ft. Gage	Formation: Describe color, texture, grain size			
" Diam. from ft. to ft. Gage	and show thickness and nature of each stratu with at least one entry for each change of forma	ım and a	quifer pe	enetrated,
PERFORATIONS: Perforated? Yes No.	position of Static Water Level and indicate prin	icipal wai	ter-beari	ng strata.
Type of perforator used 4-way Star	MATERIAL	From	То	swL
Size of perforations 3/8 in. by 1/4 in.	10PSoil	0	21/2	
750 perforations from 176 ft. to 184 ft.	BROWN CLAY	2/2	41	
80 perforations from 115 ft. to 117 ft.	Silt, Brown	41	49	
perforations from ft. to ft.	Clay Brown	49	65	
(7) SCREENS: Well screen installed? Yes X No	SI/t Brown	45	88	20
(7) SCREENS: Well screen installed? Yes No Manufacturer's Name	SAND Brown heaving	88	109	<u> </u>
Type Model No	Sand, some gravel	109	111	50
Diam. Slot size Set from ft. to ft.	SILT DARK BLUE	///	//7	
Diam. Slot size Set from ft. to ft.	SAND Fine (WOOD also)	142	142	50
	Gravel 6	168	126	50
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	Silt, Life gray	126	192	
Was a pump test made? ¥Yes ☐ No If yes, by whom?				
Yield: 550 gal./min. with 58 ft. drawdown after 25 hrs.				
" " "				
" " " " " "		<u> </u>		
Bailer test gal./min. with ft. drawdown after hrs.		 		
Artesian flow g.p.m.	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1			
erature of water 57 Depth artesian flow encountered ft.	Work started MAY 17, 19 78 Complete	ed Jun	e 8	19 78
(9) CONSTRUCTION:	Date well drilling machine moved off of well	June	8	1978
Well seal—Material used Clinen	Drilling Machine Operator's Certification:			
Well sealed from land surface to 23 ft.	This well was constructed under my	direct	super	vision.
Diameter of well bore to bottom of seal	Materials used and information reported best knowledge and belief.	above a	are true	to my
Diameter of well bore below sealin.	son in 1/ tall Kark	Date .	-5	10 78
Number of sacks of cement used in well seal sacks	(Drilling Machine Operator)	_	_	., uəz.cı.
How was cement grout placed?	Drilling Machine Operator's License No.	120		***********
The state of the s	Water Well Contractor's Certification:	-		-
- 2	This well was drilled under my jurisdi	iction an	d this r	enort is
Ween duty on the grad of West In No. 17 No.	true to the best of my knowledge and bel	ief.	-	_
Was a drive shoe used? We set no Plugs Size: location ft. Did any strata contain unusable water? Tes No	Name JW Blast Wellch	'ling	na ov	·**
Type of water? depth of strata	Address 24127 S. SKy lane D.	- Paz	LU /	 کوسی
Method of sealing strata off	1.0 1.12	i	estfi	
Was well gravel packed? Yes No Size of gravel:	[Signed] (Water Well Contr	Actor)		
	Contractor's License No. 449 Date	7	a	ران بود
Gravel placed fromfttoft.	Contractor's License No. 111 Date	une	<u> </u>	, 19. <i>L</i> .