

WATER WELL REPORT
STATE OF OREGON

RECEIVED

DEC 02 1980

WATER RESOURCES DEPT
SALEM, OREGON

CLAG
State Well No. 35/1W-32 CO

08753

State Permit No.

(1) OWNER:

Name Kenneth L Hogner
Address 23765 Butterill Rd
City Aurora State Ore

(2) TYPE OF WORK (check):

New Well ☒ Deepening ☐ Reconditioning ☐ Abandon ☐

If abandonment, describe material and procedure in Item 12.

TYPE OF WELL:

Rotary Air ☐ Driven ☐
Rotary Mud ☐ Dug ☐
Cable ☒ Bored ☐

(4) PROPOSED USE (check):

Domestic ☒ Industrial ☐ Municipal ☐
Irrigation ☐ Test Well ☐ Other ☐
Thermal: ☐ Withdrawal ☐ Reinjection ☐

(5) CASING INSTALLED:

Steel ☒ Plastic ☐
Threaded ☐ Welded ☒
" Diam. from 0 ft. to 7.0 ft. Gauge 1.250
" Diam. from ft. to ft. Gauge

LINER INSTALLED:

" Diam. from ft. to ft. Gauge

(6) PERFORATIONS:

Type of perforator used Perforated? ☐ Yes ☒ No

Size of perforations in. by in.
" perforations from ft. to ft.
" perforations from ft. to ft.
" perforations from ft. to ft.

(7) SCREENS:

Well screen installed? ☐ Yes ☒ No

Manufacturer's Name Model No.
Type Slot Size Set from ft. to ft.
Diam. Slot Size Set from ft. to ft.

WELL TESTS:

Drawdown is amount water level is lowered below static level

Was a pump test made? ☐ Yes ☒ No If yes, by whom?

Yield: gal./min. with ft. drawdown after hrs.

Test gal./min. with drill stem at ft. hrs.

Bailer test 25 gal./min. with 35 ft. drawdown after 1 1/2 hrs.

Artesian flow g.p.m.

Temperature of water Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Special standards: Yes ☐ No ☒

Well seal—Material used Cement
Well sealed from land surface to 23 ft.

Diameter of well bore to bottom of seal 10.1 in.

Diameter of well bore below seal 6 in.

Number of sacks of cement used in well seal 13 sacks

How was cement grout placed? Poured from top
No surface water around pipe

Was pump installed? Type HP Depth ft.

Was a drive shoe used? ☒ Yes ☐ No Plugs Size: location ft.

Did any strata contain unusable water? ☐ Yes ☐ No

Type of Water? depth of strata

Method of sealing strata off

Was well gravel packed? ☐ Yes ☒ No Size of gravel:

Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County Clackamas Driller's well number
SW 1/4 SW 1/4 Section 37 T. 39 R. 1W W.M.
Tax Lot # Lot Blk Subdivision

Address at well location:

Same

(11) WATER LEVEL: Completed well.

Depth at which water was first found 68 ft.

Static level 28 ft. below land surface. Date 11-8-80

Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing 6

Depth drilled 78 ft. Depth of completed well 78 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
Top Soil	0	2	
Brown Clay	2	12	
Brown Silty Clay	12	18	
Brown Clay	18	30	
Blue Clay	30	42	
Blue Silt (Dark & Fine)	42	60	
Red Shale	60	65	
Brown Shale	65	68	
Lava Hard & Broken	68	78	28

Work started Nov 4 1980 Completed Nov 8 1980
Date well drilling machine moved off of well Nov 10 1980

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] John W. Beck Date Nov 8, 1980
(Drilling Machine Operator)

Drilling Machine Operator's License No. 437

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

Name S.W. Beck Well Drilling
(Person, firm or corporation) (Type or print)

Address 24177 S. 81st Ave. Dr. Canby Ore

[Signed] John W. Beck
(Water Well Contractor)

Contractor's License No. 449 Date Nov 8, 1980

NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

WATER RESOURCES DEPARTMENT,
SALEM, OREGON 97310
within 30 days from the date of well completion.

SP-12658-690