NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310 within 30 days from the date of well completion.

0877 WATER WELL REPORT

STATE OF OREGON RECE (Pleased pe or print)
(Do not write above this line) A CState Well No. 3 State Permit No.

SP*45656

6 198N (1) OWNER: (1) OWNER:

WATER RESOURCES DEPT (10) LOCATION OF WELL:

Name FARL H. STOLLER WATER RESOURCES DEPT (10) LOCATION OF WELL:

County Theres of Charles well number. SALEM, OREGON Address RFD 3 Box 714 NE 45E 4 Section 35 T. 35 R. / W SURORA ORE Bearing and distance from section or subdivision corner (2) TYPE OF WORK (check): New Well 😿 Deepening T Reconditioning [If abandonment, describe material and procedure in Item 12. (11) WATER LEVEL: Completed well. (3) TYPE OF WELL: (4) PROPOSED USE (check): Depth at which water was first found 38 Driven 📋 Domestic 🗌 Industrial 🗎 Municipal 🗎 Static level 25 Jetted | ft. below land surface. Date 10-30-80 Bored | Irrigation Test Well Other Artesian pressure lbs. per square inch. Date (5) CASING INSTALLED: Threaded | Welded 12 " Diam. from 0 ft. to 205 ft. Gage ... 250 (12) WELL LOG: Diameter of well below casing ... Depth drilled 205 ft. Depth of completed well 205 .." Diam. fromft. to ft. Gage Formation: Describe color, texture, grain size and structure of materials; " Diam. from _____ ft. to ____ ft. Gage ____ and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in (6) PERFORATIONS: position of Static Water Level and indicate principal water-bearing strata. Perforated? Yes No. Type of perforator used STAR MATERIAL te of perforations in. by 3/8 IOPSCIL 3 perforations from 156 ft. to 188 LAY BROWN 3 38 perforations from _____ft, to BROWN 75 30*4* perforations from GREY 75 83 BROWN 92 (7) SCREENS: Well screen installed?

Yes ILTY CLAY DARK GREY 92 109 Manufacturer's Name FINE BLACK 109 111 GREV 111 Diam. Slot size Set from SANDS TONE 124 133 Diam. Slot size Set from 133 142 EMBUT GRAVEL 142 (8) WELL TESTS: Drawdown is amount water level is lowered below static level AND E GRAVEL 152 192 a pump test made? Wes I No If yes, by whom? DRILLER FINE GREY 192 201 field: 570 gal./min. with 52 ft. drawdown after 3 hrs. BLUE STICKEY 201 205 r test gal./min. with ft. drawdown after Artesian flow g.p.m. Temperature of water Depth artesian flow encountered Work started Oct 21 1980 Completed Nov 2 1980 Date well drilling machine moved off of well Nov2 (9) CONSTRUCTION: 19 80 Drilling Machine Operator's Certification: Diameter of well bore to bottom of seal _____in. Diameter of well bore below seal ______in. Number of sacks of cement used in well seal 18 How was cement grout placed? Jump Drilling Machine Operator's License No. Water Well Contractor's Certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Was a drive shoe used? Yes 🗌 No Plugs Size: location ft. Did any strata contain unusable water?

Yes Type of water? Method of sealing strata off Was well gravel packed? Yes No Size of gravel: Contractor's License No. .743. Date Nov 2 , 1980 (USE ADDITIONAL SHEETS IF NECESSARY)