617 - 1 - 117 - 12 - 12 - 12 - 12 - 12 -	ELL REPORT (8776	- 1	–	.
STATE COLUMN OR STATE OF WITHIN 30 days from the date of well completion. ALLIM ORFOLIA (Do not write	OF OREGON (State Well No. State Permit I			
(1) OWNER:	(11) LOCATION OF WELL:			
Name Harold Langdon	County Clackamas Driller's well number			
Address 55 N.W. 139th Ave.	14 14 Section 35 T.3S R. 1W W.M.			
Portland, Oregon (2) TYPE OF WORK (check):	Bearing and distance from section or subdivision corner			
New WellAT				
New Well Deepening Reconditioning Abandon Standard Reconditioning Abandon Standard Reconditioning Reconditionin				
(3) TYPE OF WELL: (4) PROPOSED USE (check): Rotary Driven Domestic Industrial Municipal Domestic Municipal Domestic Domestic	(12) WELL LOG: Diameter of well below casing 14			
Dug 🗌 Bored 🗎 Irrigation 🍱 Test Well 🗌 Other 📋	Depth drilled 220 ft. Depth of completed well 220 ft.			
CASING INSTALLED: Threaded Welded 14 " Diam. from 0 ft. to 155 ft. Gage 15td. Threaded Welded 15td.	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level as drilling proceeds. Note drilling rates.			
" Diam, fromft. toft. Gage	MATERIAL	From	То	SWL
	Top soil -	0	_2	
PERFORATIONS: Perforated? Yes \(\subseteq \text{No.} \)	clay- brown- sandy	2	60	ļ
e of perforator used torch	sand- clay- brown (with streaks of gravel)	60	125	
Size of perforations in. by 4 in.	clay - brown- sticky	125	131	
127 perforations from 165 ft. to 145 ft. 313 perforations from 215 ft.	clay - brown - sandy	131		
ft.	sand - brown	133		
perforations fromft. toft.	clay-blue-(sandy-gravel			
perforations from ft. to ft	and rock)	145	152	
	silt- blue black- sandy			
(7) SCREENS: Well screen installed? Yes No	with small gravel & wood	152	165	55
Manufacturer's Name	well tested 300 gals. per	Min.		
Type	at this depth, with 140 ft	MILLI	·	
Diam. Slot size Set from ft. to ft. Diam. Slot size Set from ft. to ft.	draw down.		198_	
	cemented gravel	165		
(8) WATER LEVEL: Completed well.	sand- gray	198	215	
Static level 45 ft. below land surface Date 3/24/6				
an pressure lbs. per square inch Date	going into gray clay	215	220	
(9) WELL TESTS: Drawdown is amount water level is lowered below static level				
Was a pump test made? Yes \(\subseteq \text{No If yes, by whom?} \)				
Yield: 800 gal./min. with 68 ft. drawdown after 45Min	Work started Oct. 14 19 68 Complete	dMar.	25	19 69
550 " 64 " 2 hrs	Date well drilling machine moved off of well	?		19 #
" " "	Drilling Machine Operator's Certification:			
Bailer test gal./min. with ft. drawdown after hrs.	This well was constructed under my direct appropriate as			
Artesian flow g.p.m. Date	rials used and information reported above are true to my best knowledge and belief			
Temperature of water Was a chemical analysis made? ☐ Yes ☐ No	[Signed]	<i>a</i> / =	121	69
	(Drilling Machine Operator)	Date	/WD	ر <u>ب</u> 19
(10) CONSTRUCTION: Well seed Metantal and Be tonite	Drilling Machine Operator's License No			
Well seal—Material used Betonite Depth of seal 25				
Diameter of well bore to bottom of seal 18 in.	Water Well Contractor's Certification:			
Were any loose strata cemented off? Yes No Depth	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.			
Was a drive shoe used? Yes No	NAME Barron & Strayer			
Did any strata contain unusable water? Yes X No	(Person, firm or corporation) (Type or print)			
Type of water? depth of strata	Address Rt.1, Box 254, Beaverton, Ore.97005			
Method of sealing strata off	and all and and and			
Was well gravel packed? ☐ Yes XNo Size of gravel:	[Signed] (Water Well Contractor)			
Gravel placed fromft. toft.	Contractor's License No. 35 Date Mg	ar.31	1	₁₉ 69
(USE ADDITIONAL SHEETS IF NECESSARY)				