	#1 - North Bound
CI AC	The first page in
NOTICE TO WATER WELL CONTRACTOR	008780 345
The original and first copy	TIL REPORT
of this report are to be filed with the STATE ENGINEER, SALEM, OREGON 97819 STATE O	F OREGON State Well No. 3/16-
STATE ENGINEER, SALEM, OREGON 97310 STATE OF OREGON within 30 days from the date of well completion. State Permit No	
(1) OWNER:	(11) WELL TESTS: Drawdown is amount water level is lowered below static level
NamORESTATE HIGHWAY LEPT:	Was a pump test made? Wyes \(\subseteq \text{No If yes, by whom? STRASSER} \)
Address WILSONVILLE REST AREA	Yield: 54 gal./min, with 17 ft. drawdown after 4 hrs.
(a) LOCATION OF WINE 112 10 /	" " " " "
(2) LOCATION OF WELL: WELL NO. /	
County CLACK, Driller's well number 4/28	Bailer test gal./min. with ft. drawdown after hrs. Artesian flow g.p.m. Date
NW4 5E4 Section 26 T. 35 R. 1W W.M.	Temperature of water 54 Was a chemical analysis made? Yes You
Bearing and distance from section or subdivision corner	(12) WELL LOG; Diameter of well below casing 6/NCH
	Depth drilled .#73 ft. Depth of completed well /73 ft.
	Formation: Describe by color, character, size of material and structure, and
	show thickness of aquifers and the kind and nature of the material in each stratum penetrated, with at least one entry for each change of formation.
(2) TYPE OF WORK (11).	MATERIAL FROM TO
(3) TYPE OF WORK (check):	TOP 3014 05
New Well Deepening Reconditioning Abandon	SANDY CLAY 5 81
andonment, describe material and procedure in Item 12.	BROWN SAND 81 118
(4) PROPOSED USE (check): (5) TYPE OF WELL:	GRAVEL AND SAND 118 139
Domestic ☐ Industrial ☐ Municipal ☐ Rotary ☐ Driven ☐	BROWN SAND AND GRAVEL 139 153
Irrigation ☐ Test Well ☐ Other ☐ Cable ☑ Jetted ☐ Dug ☐ Bored ☐	GREY JAND, SOME CHRAVEL 153 162
(6) CASING INSTALLED.	BLUE CLAY /62/96
777	
"Diam. from ft. to ft. Gage" The diam. from ft. to ft. Gage	
"Diam. from ft. to ft. Gage ft	
(7) DEDEOD ATIONS	
Tentorated Maries 10	
Type of perforator used 57AR	
Size of perforations 3/8 in. by //4 in. ———————————————————————————————————	
perforations from ft. to ft.	
(8) SCREENS: Well screen installed? ☐ Yes 🕍 No	
Manufacturer's Name	
Twoe Model No.	
1	Work started APR 2/19 66 Completed MAY 191866
Diam Slot size Set from ft. to ft.	Date well drilling machine moved off of well
(9) CONSTRUCTION:	(13) PUMP:
Well seal—Material used in seal BENTONITE	No.
Depth of seal	Manufacturer's Name
Diameter of well bore to bottom of seal $\frac{1}{2}$ in,	Type: H.P.
Were any loose strata cemented off? Yes No Depth	Water Well Contractor's Certification:
Was a drive shoe used? X Yes □ No	This well was drilled under my jurisdiction and this report is
Was well gravel packed? Yes No Size of gravel:	true to the best of my knowledge and belief.
Gravel placed from ft. to ft.	NAME KI STRASSER DRILLING (O. (Person, firm or corporation) (Type or print) Address 8/10SE SUNSET LANE FORTLAND ORD
Did any strata contain unusable water? Yes No	(Person, firm or corporation) (Type or print)
Type of water? depth of strata	Address J. I. U. JE JUNDET KANE FORTLAND OKE
Method of sealing strata off	Drilling Machine Operator's Ligense No
(10) WATER LEVELS:	18 mad Robert & Harrison
Static level 65 ft. below land surface Date MAY 17/166	(Water Well Contractor)
Artesian pressure lbs. per square inch Date	Contractor's License No. 10 Date MAY 27 1066