NOTICE TO WATER WELL CONTRACT RECEWATER WELL REPORT QUE The original and first copy of this report are to be filed with the STATE ENGINEER, SALEM, OREGON 97310 OCT 22 1986ATE OF OREGON WATER RESOURCES DETENDED OF PRINT AUG 2 3 1976 CONTINUE AUG 2 3 19 within 30 days from the date (1) OWNER: Name Sam Gotter Realators Clicking E20Niller's well number Address P.O. Box 23023 Tigard, Oregon Bearing and distance from section or subdivision corner (2) TYPE OF WORK (check): New Well [X Deepening [Reconditioning | Abandon 🔲 If abandonment, describe material and procedure in Item 12. (11) WATER LEVEL: Completed well. (3) TYPE OF WELL: (4) PROPOSED USE (check): Depth at which water was first found 65 trace Rotary Driven 🗆 Domestic 🕱 Industrial 🗌 Municipal 🗍 Cable Static level 370 ft. below land surface. Date 7-29-76 Jetted [7] Dug Bored | Irrigation ☐ Test Well ☐ Other Artesian pressure lbs. per square inch. Date CASING INSTALLED: ASING INSTALLED: Threaded Welded 28 280 (12) WELL LOG: Diameter of well below casing Depth drilled 540 ft. Depth of completed well " Diam. from _____ ft. to ____ ft. Gage ___ Formation: Describe color, texture, grain size and structure of materials; _____ft. to ______ft. Gage _____ and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in PERFORATIONS: position of Static Water Level and indicate principal water-bearing strata. Perforated? Tyes Di No. Type of perforator used MATERIAL Size of perforations in, by in, Top soil 0 2 perforations from ______ft. to _____ft. Brown clay 2 17 perforations from _____ ft. to _____ ft. Brown broken rock perforations fromft. to Blue med. tock 27 47 Brown lava rock (7) SCREENS: 65 Well screen installed? ☐ Yes ☑ No Blue basalt 65 110 Manufacturer's Name Brown lava rock 110 120 Model No. Gray med. rock 120 185 Diam. Slot size Set from ft. to Brown rock 185 190 Diam. Slot size Set from ft. to ft. Blue basalt 190 210 Drawdown is amount water level is lowered below static level (8) WELL TESTS: Brown rock 210 222 Blue basalt 222 265 Was a pump test made?
Yes No If yes, by whom? Brown med, rock 265 285 gal./min. with ft. drawdown after Blue med. rock 285 408 Brown lava rock 408 420 Blue basalt 420 #ir Brown lava rock 455 Bar test 465 gal./min. with 155ft. drawdown after 1 Blue basalt 465 530 Brown Fock Work started 7-22-76 19 perature of water Depth artesian flow encountered Completed 27029276 (9) CONSTRUCTION: Date well drilling machine moved off of well Well seal-Material used Cement Drilling Machine Operator's Certification: This well was constructed under my direct supervision. Materials used and information reported above are true to my Well sealed from land surface to _______28 Diameter of well bore to bottom of seal _____9 in. best knowledge and belief. Diameter of well bore below seal _____6__ in. [Signed] Mth Date 8-2-76 19 (Drilling Machine Operato Number of sacks of cement used in well seal Drilling Machine Operator's License No.254 Number of sacks of bentonite used in well seal .____ Brand name of bentonite Water Well Contractor's Certification: Number of pounds of bentonite per 100 gallons This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Was a drive shoe used? 🗌 Yes 🕱 No Plugs Size: location ft. Name Ralph Turner Drilling Co. Did any strata contain unusable water? 🗌 Yes 🗶 No (Person, firm or corporation) (Type or print) Type of water? _____dep<u>th</u> of strata Address Rte 1 Box 141 Hillshord, Oregon Method of sealing strata off Was well gravel packed? ☐ Yes 🏿 No Size of gravel: ... Gravel placed from Contractor's License No.242 ... Date8-2-76, 19...... (USE ADDITIONAL SHEETS IF NECESSARY)