NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 9731/0 O within 30 days from the date of well completion.

WATER WELL REPORT B 2 1 1973

C STATE OF OREGONTE ENGINEER

(Please type or print) SALEM. OREGON tate Permit No.

(Do not write above this line)

6-71.03

(1) OWNER:	(10) LOCATION OF WELL:
Name LAKE GROVE GARNEN CENTER	County CLACK Driller's well number 5432
Address Pc. Box 1488	5W 1/4 5W/4 Section 6 T. 3 S R. / E W.M.
LAKE GROVE ORE, 97034	Bearing and distance from section or subdivision corner
(2) TYPE OF WORK (check):	and diseased from section of subdivision corner
New Well ☐ Deepening X Reconditioning ☐ Abandon ☐	The state of the s
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 2/8
Rotary Driven Domestic M Industrial D Municipal	124
Cable	78/75
	Artesian pressure lbs. per square inch. Date
(5) CASING INSTALLED: Threaded □ Welded □	(12) WELL LOG: Diameter of well below casing
ft. toft. Gage	Denth drilled 204 & Denth of well below cashing
" Diam. from ft. to ft. Gage	Formation: Describe color, texture, grain size and structure of materials;
" Diam. fromft. toft. Gage	and show thickness and nature of each stratum and aquifer penetrated
PERFORATIONS: Perforated? Yes Yo.	with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.
Type of perforator used	
Size of perforations in. by in.	Trom To SWI
perforations fromft_ toft_	HARD CIREY BASALT 170 182
perforations from ft. to ft.	MEDHARD GRAY BASAIT 182 218 DOROUS FLACK BASAIT 218 227
perforations fromft. toft.	BROWN BASALT 218 227
(E) CCDPTIC	HARD GREY BASALT 236 185
(7) SCREENS: Well screen installed? Yes X No	BROKEN GREY BASALT 285 294
Manufacturer's Name TypeModel No.	HARD GREY BASALT 294 304
Diam. Slot size Set from ft. ft. Diam. Slot size Set from ft. ft.	
Det Holl II. 10 II.	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	
Was a pump test made? Yes XNo If yes, by whom?	
gai./min. with it. drawdown after hrs.	
" " "	
Bailer test 2/ gal/min with 3 ft drawdown after / has	
gar, mar with a day down alter mis.	
esian flow g.p.m.	
perature of water Depth artesian flow encountered ft.	Work started 2/7 1973 Completed 2/9 1973
(9) CONSTRUCTION:	Date well drilling machine moved off of well 2/9 1973
Well seal-Material used PREVIDUSLY SEALED,	Drilling Machine Operator's Certification:
Well sealed from land surface toft	This well was constructed under my direct supervision
Diameter of well bore to bottom of seal in.	Materials used and information reported above are true to my best knowledge and belief.
Diameter of well bore below seal in.	[Signed] Thurs I shoul Date 2/19, 1973
Number of sacks of cement used in well seal sacks	(Drilling Machine Operator)
Number of sacks of bentonite used in well seal sacks	Drilling Machine Operator's License No. 5.6.4
Brand name of bentonite	Water Well Contractor's Certification:
Number of pounds of bentonite per 100 gallons	•
of waterlbs./100 gals.	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Was a drive shoe used? ☐ Yes No Plugs Size: location ft. Did any strata contain unusable water? ☐ Yes No	Name KJSTEASSER VEILLING CO
7.00	Address 8/105E SUNSET, LAWE FORTIAND OF
Type of water? depth of strata	Address 8110SE SONSET LANE FORTLAND ORE
Method of sealing strata off	[Signed] Kally T. Thassir
Was well gravel packed? ☐ Yes No Size of gravel:	(Water Well Contractor)
Gravel placed fromft. toft.	Contractor's License No. Date #EB 19, 1973
(USE ADDITIONAL SH	EETS IF NECESSARY)