NOTICE TO WATER WELL CONTRACTOR
The original and first copy
of this report are to be
filed with the

CLAC STATE OF ORE PINE OF 1970 Please type or print JUL - 1 1970 State Permit No.
Mo not write above this line ENGINEER EALEM DREGON

	(10) TO AMON OF WELL:		
(1) OWNER:		mbon /c	-8
Name BILL KAISER			*** 3.5
Address RT 1 Box 567-I	5E 14 NW 1/4 Section 16 T. 35		<u>W.M.</u>
WEST LINN OREGON	Bearing and distance from section or subdivisio	n corner	
(2) TYPE OF WORK (check):			- 14 to 5 7 7 7 -
New Well X Deepening □ Reconditioning □ Abandon □	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed we	:II. _	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found	<u>57 </u>	ft.
Rotary Driven Domestic Industrial Municipal	Static level 62 ft. below land st	ırface. Date	e
Cable X Jetted ☐ Irrigation ✓ Test Well ☐ Other ☐	Artesian pressure lbs. per square	inch. Date	е —
CASING INSTALLED: Threaded Welded So C Diam. from C ft. to 540 ft. Gage 250 C Diam. from ft. to ft. Gage C C C C C C C C C	(12) WELL LOG: Diameter of well be Depth drilled 725 ft. Depth of complete formation: Describe color, texture, grain size a and show thickness and nature of each stratum with at least one entry for each change of format position of Static Water Level and indicate prince	nd structure n and aquif- ion. Report	ft. e of materials; for penetrated, each change in
	MATERIAL		To SWL
Type of perforator used	Top Soil	0	1
Size of perforations in. by in.	BROWN CLAY		6
perforations fromft. toft.	SANDY BROWN CLAY	16 2	O
perforations fromft, toft.	BROWN CLAY		6
perforations from	BRIDWN CLAY SOME GRAVEL	36 4	
(7) SCREENS: Well screen installed? Yes Y No	BROWN CLAY	44 5	7
	BROWN CLAY AND GRAVEL		5 30
Manufacturer's Name	SOFT BROWN SANDSTONE		30
Diam. Slot size Set from ft. to ft.	BLUE CLAY		13
Diam. Slot size Set from ft. to ft.	BROWN CLAY		04
Diam. Slot size	BILLE CLAY	104 3	10
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	BROWN CLAY		20
TOWCLOR BULL NORTH TO THE	BLUE CLAY	320 5	508
Was a pump test made? Yes No If yes, by whom?	BROWN CLAY		140
Yield: gal./min. with ft. drawdown after hrs.	BECOMPOSED BASALT	540 5	44 62
	SOFT BROWN BASALT		60 62
" " " " " " " " " " " " " " " " " " " "	MED HARD BROWN		
Bailer test 45 gal./min. with 70 ft. drawdown after hrs.	BASALT	560 5	585 62
Artesian flow g.p.m.	HARD BASALT	5856	18 62
experature of water 5/ Depth artesian flow encounteredft.	Work started 3-6 1970 Complet	ed 57	18 1970
Gerature of water of Dopan arcasan	Date well drilling machine moved off of well		8 1970
(9) CONSTRUCTION:	Drilling Machine Operator's Certification:		
Well seal—Material used BENTONITE Well sealed from land surface to 30 ft. Diameter of well bore to bottom of seal 13 in. Diameter of well bore below seal 10 in. Number of sacks of cement used in well seal sacks	This well was constructed under my Materials used and information reported best knowledge and belief.	direct s above are	e true to my -29, 19.70
Number of sacks of peritornic discussion and a sack of the sacks of peritornic discussion and a sack of the sacks of peritornic discussion and a sacks of perit			
Dianu name of bentome assessment	Water Well Contractor's Certification:		
Number of pounds of bentonite per 100 gallons	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.		
Was a drive shoe used? Yes No Pugs Size: location ft.	Value Walling Co.		
Did any strata contain unusable water! \(\subseteq \text{Yes \textsize No} \)	Name (Person, firm or corporation) (Type or print)		
Type of water? depth of strata	Address 5365 S.E. HILLWOOD	וי/ורה	NAUKIE
Method of sealing strata off	[Signed] Sekelle		
Was well gravel packed? ☐ Yes No Size of gravel:	(Water Well Cont	ractor)	•
Gravel placed fromft.	Contractor's License No. 462 Date	6-29	
Graver parece atom	The second secon		