NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310 within 30 days from the date of well completion.

RECEIVED
FEB 13 1979
WATER RESOURCES DEPT.
SALEM, OREGON

WATER WELL REPORT
STATE OF OREGON
(Please type or print)
(Do not write above this line)

CLAC 009466

State Well No. 3s/1E-21cc

State Permit No.

(1) OWNER:
Name Duane Weeks
Address 3185 N. Holly, Canby, Oregon 97013

(2) TYPE OF WORK (check):
New Well ☒ Deepening ☐ Reconditioning ☐ Abandon ☐
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:
Rotary ☒ Driven ☐
Cable ☐ Jetted ☐
Dug ☐ Bored ☐

(4) PROPOSED USE (check):
Domestic ☐ Industrial ☐ Municipal ☐
Irrigation ☒ Test Well ☐ Other ☐

(5) CASING INSTALLED:
Threaded ☐ Welded ☒
8 " Diam. from 0 ft. to 477 ft. Gage .250
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

(6) PERFORATIONS:
Perforated? ☐ Yes ☒ No
Type of perforator used
Size of perforations in. by in.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS:
Well screen installed? ☐ Yes ☒ No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:
Drawdown is amount water level is lowered below static level
Was a pump test made? ☐ Yes ☒ No If yes, by whom?
Yield: 200 gal./min. with total ft. drawdown after 4 hrs.
" " " "
" " " "
Bailer test gal./min. with ft. drawdown after hrs.
Artesian flow g.p.m.
Temperature of water Depth artesian flow encountered ft.

(9) CONSTRUCTION:
Well seal—Material used cement
Well sealed from land surface to 18 ft.
Diameter of well bore to bottom of seal 12 in.
Diameter of well bore below seal 8 in.
Number of sacks of cement used in well seal 12 sacks
How was cement grout placed? poured
Was a drive shoe used? ☒ Yes ☐ No Plugs Size: location ft.
Did any strata contain unusable water? ☐ Yes ☒ No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? ☐ Yes ☒ No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:
County Clackamas Driller's well number D-181-79
SW ¼ SW ¼ Section 21 T. 3S R. 1E W.M.
Bearing and distance from section or subdivision corner
tax lot 1400

(11) WATER LEVEL: Completed well.
Depth at which water was first found 98 ft.
Static level 60 ft. below land surface. Date 1-30-79
Artesian pressure lbs. per square inch. Date

(12) WELL LOG:
Diameter of well below casing 8"
Depth drilled 480 ft. Depth of completed well 480 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
topsoil	0	6	
sandy clay-brown	6	98	
gravel-med-sand-water	98	105	
blue clay	105	113	
sand-black-water	113	118	
clay-blue	118	267	
sand-black	267	277	
clay-blue	277	292	
clay-gray	292	450	
sand-black-water	450	480	

Work started 1-18 19 79 Completed 1-30 19 79
Date well drilling machine moved off of well 1-30 19 79

Drilling Machine Operator's Certification:
This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] David Donnelly (Drilling Machine Operator) Date 2-6, 1979
Drilling Machine Operator's License No. 883

Water Well Contractor's Certification:
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name S & M Drilling & Supply, Inc. (Person, firm or corporation) (Type or print)
Address 399 S. Walnut, Canby, Oregon 97013
[Signed] Walter Mac (Water Well Contractor)
Contractor's License No. 497 Date 2-6, 1979

(USE ADDITIONAL SHEETS IF NECESSARY)

SP*45656-119