

NOTICE TO WATER WELL CONTRACTOR: The original and first copy of this report are to be filed with the

RECEIVED SEP 22 1978

WATER WELL REPORT

WATER RESOURCES DEPARTMENT, SALEM, OREGON, WATER RESOURCES DEPT., STATE OF OREGON (Please type or print) SALEM, OREGON (Do not write above this line)

CLAC 009601

State Well No. 35/1E-25bb State Permit No.

(1) OWNER:

Name John Emery Address 113 Foothills Rd. Lake Oswego, Oregon 97034

(2) TYPE OF WORK (check):

New Well [X] Deepening [] Reconditioning [] Abandon [] If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary [X] Cable [] Dug [] Driven [] Jetted [] Bored []

(4) PROPOSED USE (check):

Domestic [X] Industrial [] Municipal [] Irrigation [] Test Well [] Other []

CASING INSTALLED:

6" Diam. from 0 ft. to 75 ft. Gage .250

PERFORATIONS:

Type of perforator used Size of perforations in. by in. perforations from ft. to ft.

(7) SCREENS:

Well screen installed? [] Yes [X] No Manufacturer's Name Type Model No. Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level Was a pump test made? [] Yes [X] No Yield: 40 gal./min. with total ft. drawdown after 1 hrs.

(9) CONSTRUCTION:

Well seal—Material used cement Well sealed from land surface to 18 ft. Diameter of well bore to bottom of seal 10 in. Diameter of well bore below seal 6 in. Number of sacks of cement used in well seal 6 sacks How was cement grout placed? poured

(10) LOCATION OF WELL:

County Clackamas Driller's well number D-161-78 NW 1/4 NW 1/4 Section 25 T. 3S R. 1E W.M. Bearing and distance from section or subdivision corner Tay Lot 500

(11) WATER LEVEL: Completed well.

Depth at which water was first found 74 ft. Static level 30 ft. below land surface. Date 9/13/78 Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing 6" Depth drilled 75 ft. Depth of completed well 75 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

Table with columns: MATERIAL, From, To, SWL. Rows include Topsoil, Clay Brown, Clay Gray Sandy, Clay Blue, Sand Black Water Bearing.

Work started 9/12 1978 Completed 9/12 1978 Date well drilling machine moved off of well 9/12 1978

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief. [Signed] Brian Blocker Date 9/12/78

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Name S7M Drilling & Supply Inc. Address 399 SE Walnut St Canby, Oregon 97013 [Signed] Walter Mace Date 9/12/1978