NOTICE TO WATER WELL CONTRACTOR OF The original and first copy of this report are to be SEP 1 WATER WELL REPORT filed with the STATE ENGINEER, SALEM, OREGON 97310 STATE OF OREGON within 30 days from the date of well completion. (Please type or print)

State Well No.

of well completion.	State Permit No)*************************************	
(1) OWNER:	(11) WELL TESTS: Drawdown is amount water level is lowered below static level		
Name Clarence Lepinsky	Was a pump test made? Yes Yo If yes, by whom?		
Address 260 Wait Ave.	Yield: gal./min. with ft. drawdow		hrs
Canby, Ore,	" " "	II WATER	
(2) LOCATION OF WELL:	" " "		,,
	Bailer test 3() gal./min. with 1 ft. drawdo	un ofter 7	hrs
County Clackmas Driller's well number 3/1-27H	Artesian flow g.p.m. Date	wir dritter j	
1/4 Section T. R. W.M.			
Bearing and distance from section or subdivision corner	(10) THELL TOC		
	Diameter of well below eas	ing	**********
	Depth drilled 76 ft. Depth of completed well	1 76	ft
	Formation: Describe by color, character, size of material	and structur	re, and
	Formation: Describe by color, character, size of material show thickness of aquifers and the kind and nature of the stratum penetrated, with at least one entry for each character.	ange of forn	n eaci nation
	MATERIAL	FROM	mo.
(3) TYPE OF WORK (check):	Silty sand		TO
New Well Deepening □ Reconditioning □ Abandon □	Anderstan holdens make		<u>ò</u>
andonment, describe material and procedure in Item 12.	Andesite bolders not water	6 4	6
	Cement gravel	12 3	
(4) PROPOSED USE (check): (5) TYPE OF WELL:		46 5	
Domestic Industrial Municipal Rotary Driven	Yellow silty sand with small	52 7	1
Irrigation ← Test Well □ Other □ Cable 1 Jetted □ □ Dug □ Bored □	Very coarse gravel & arn		
(A) CACING THOMAS TO			
	Black gand	$\frac{71}{2}$	
65/8" Diam from 1-0 ft. to 76 ft. Gage 250	Black sand	75 76	<u>5</u>
"Diam. fromft. toft. Gage			
" Diam. from ft. to ft. Gage			
(7) PERFORATIONS: Perforated? ☐ Yes 및 No			
Type of perforator used			
Size of perforations in. by in.			
perforations from ft. to ft.			
perforations fromft. toft.			
perforations fromft. toft.			
perforations fromft. toft.			
perforations fromft. toft			
(0) ((0)			
(8) SCREENS: Well screen installed? ☐ Yes ☐ No			
Manufacturer's Name			
Type Model No.			
Slot size ft. to ft.	Work started 8/23/66 19 Completed 8	122 166	
Diam. Slot size Set from ft. to ft.	Date well drilling machine moved off of well	/31/66	
(9) CONSTRUCTION:	(13) PUMP:		19
	(10) I CMI:		
Well seal—Material used in seal Drill cuttings & Bentonit	Manufacturer's Name		
Depth of seal 18 ft. Was a packer used? Bentonit	Type:	P	
Diameter of well bore to bottom of seal in.	Water Well Contractor's Certification:		
Were any loose strata cemented off? Yes No Depth			
Was a drive shoe used? Y Yes □ No	This well was drilled under my jurisdiction ar	d this repo	ort is
Was well gravel packed? Tyes Tho Size of gravel:	true to the best of my knowledge and belief.		
Gravel placed fromft.	NAME Harry A. Robinson		
Did any strata contain unusable water? No	NAME Harry A Robinson (Person, firm or corporation) (Type or print)		
Type of water? depth of frata	Address 2214 Front St NE Salem, Ore		
Method of sealing strata off	Drilling Machine Operator's License No63	-	
(10) WATER LEVELS:		***************************************	*******
Static level 42 ft. below land surface Date 9/1/66	[Signed] Alabaman		
	(Water Well Contractor)		
	Contractor's License No. 22 Date 9/1/66	Ĵ 19	}
(USE ADDITIONAL SH	EETS IF NECESSARY)		