NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report
are to be filed with the

WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310 within 30 days from the date of well completion.

## WATER WELL REPORT

STATE OF OREGON CLAC

(Please type or print) 009705

State Well No. 35/E-38
State Permit No.

(1) OWNER:	(10) LOCATION OF WELL:	
Name Joe Sisul	County Clackamas Driller's well number D336-80	
Address 2965 N. Holly	14 14 Section 28 T. 3S R. 1E W.M.	
Canby, Oregon 97013	Bearing and distance from section or subdivision corner	
(2) TYPE OF WORK (check):	drilled at mailing address	
New Well XX Deepening  Reconditioning  Abandon		
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed w	الم
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Don'th of reliab restaurant to 1.5	
RotaryXX Driven Domestic D Industrial Municipal D		- U
☐ Jetted ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐		urface. Dat $10/18/80$
	Artesian pressure lbs. per squar	e inch. Date
(5) CASING INSTALLED:  8	(12) WELL LOG: Diameter of well below casing	
" Diam. fromft. toft. Gage		
(6) PERFORATIONS: Perforated XX Yes □ No.		
Type of perforator used torch	****	sipai water-pearing strata.
a: 1 1 2 1 2 1 2 1 1 C	MATERIAL	From To SWL
100 perforations from 233 ft. to 255 ft.	topsoil	0 2 2 47
perforations fromft. toftftft.	clay brown sandy clay blue sticky	
perforations from	sand black wter/bear	<b>2</b> 47 123 123 123 130
	clay blue sticky	130 145
(7) SCREENS: Well screen installed? ☐ YeXX☐ No	sand black water/bear	145 153
Manufacturer's Name	clay blue sandy	153 204
TypeModel No.	clay blue sand water bea	
Diam. Slot size Set from ft. to ft.	sandstone & claystone	243 260
Diam. Slot size Set from ft. to ft.	water bearing	105
(8) WELL TESTS: Drawdown is amount water level is lowered below static level		
lowered below static level	DECENTED	
s a pump test made?  Yes XX No If yes, by whom?		
Yield: 150 gal./min. with total drawdown after l hrs.	OCT 2 1 1980	
" air rotary	WATER RESOURCES DEPT	
" all loca, y " "	SALEM, OREGON	
iler test gal./min. with ft. drawdown after hrs.		
Artesian flow g.p.m.		
Temperature of water Depth artesian flow encounteredft.	Work started 10/14/809 Completes	10/16/00
		10/16/80 19
(9) CONSTRUCTION:		10/16/80 19
Well seal—Material used Cement	Drilling Machine Operator's Certification:	
Well sealed from land surface to 18 ft.	This well was constructed under my direct supervision.  Materials used and information reported above are true to my	
Diameter of well bore to bottom of seal 14 in.	best knowledge and belief.	
Diameter of well bore below seal8in.  Number of sacks of cement used in well seal16	[Signed] . Marking Machine Operator) Date 10/16/80	
Number of sacks of cement used in well seal 16 sacks How was cement grout placed? pressure grouted	Drilling Machine Operator's License No1169	
	Water Well Contractor's Certification:	
Sign Control of the C	This well was drilled under my jurisdiction and this report is	
Was a drive shoe used XX Yes 🗌 No Plugs Size: locationft.	true to the best of my knowledge and belief.	
Did any strata contain unusable water? TYXX No	Name S & M Drilling & Supply  (Person, firm or corporation) (Type or print)	
Type of water? depth of strata	Address 399 S E Walnut Cnaby, Ore 97013	
Method of sealing strata off	11/4/201	
Was well gravel packed? TYXX No Size of gravel:	[Signed] (Water Well Contractor)	
Gravel placed fromft to ft.	Contractor's License No497. Date10	
	TaleTC	<i>.</i>