NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

WATER WELL REPORT E C I V State yell No.

STATE ENGINEER, SALEM, OREGON of well completion.

Method of sealing strata off

Gravel placed from 190 ft. to

Was well gravel packed? □ ¥es □ No Size of gravel: #6 & 1/8

(Please type or print)

AUG9 197 Gate Permit No. 35/11-(Do not write above this line)
VATER RESOURCES DEPT. within 30 days from the date (10) LOCATION OF WELL: (1) OWNER: County Clackamas Driller's well number Industrial Forrestry Assoc. 1887 N. Holly St., Canby, Ore. w.m. 28 т. 3S R. NW 14 SW 14 Section Bearing and distance from section or subdivision corner (2) TYPE OF WORK (check): New Well Deepening [ Reconditioning [ Abandon 🔲 If abandonment, describe material and procedure in Item 12. (11) WATER LEVEL: Completed well. (3) TYPE OF WELL: (4) PROPOSED USE (check): Depth at which water was first found Rotary Driven [ Domestic | Industrial | Municipal | Static level ft. below land surface. Date Jetted | Cable Irrigation ★ Test Well □ Other Dug Bored Artesian pressure lbs. per square inch. Date CASING INSTALLED: Threaded Welded XX (12) WELL LOG: Diameter of well below casing ...10 ..." Diam. from ...... ft. to ..... ft. Gage ..... 285 Depth drilled ft. Depth of completed well Formation: Describe color, texture, grain size and structure of materials; .." Diam. from .Closedft. to Bottom ft. Gage ..... and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata. PERFORATIONS: Perforated? XXYes \( \Bar\) No. Type of perforator used Mills Knife MATERIAL From SWI. Size of perforations 12" in, by Top soil, br., sandy 0 2 Sand, br., compacted 22 Gravel, med., sand, coarse 608 perforations from 168 ft. to 130 ft. Gravel, lrg., small boulders 72 75 perforations from .... 75 Clay, grey (7) SCREENS: Well screen installed? XXYes □ No Gravel, med., cemented 77 87 Manufacturer's Name Johnson Stainless Steel Clay, grey, sandy 98 87 ... Model No. .. Gravel , med. w/sand 98 104 Clay, grey, seams, sand 104 117 Sand, gravel w/clay 117 124 124 Clay, blue, sticky 133 Drawdown is amount water level is lowered below static level (8) WELL TESTS: Sand, blue, med., water 133 160 Was a pump test made? Q Yes \( \subseteq No \) If yes, by whom? Driller Clay, blue, sandy Ī60 163 Sand, black Yield: 600 gal./min. with 85 ft. drawdown after 4½ hrs. 163 167 Clay, blue 167 195 550 78 30 min 500 Sand, black 195 225 68 lhr.15min. SAndstone black trace wtr 225 245 ft. drawdown after Bailer test gal./min. with Sand Stone black Artesian flow g.p.m.\_ perature of water Depth artesian flow encountered .. Work started 19 76 Completed <u>3–8 </u> 7-22 Date well drilling machine moved off of well (9) CONSTRUCTION: **Drilling Machine Operator's Certification:** Cement Grout Well seal-Material used ...... This well was constructed under my direct supervision. 90' Well sealed from land surface to .. Materials used and information reported above are true to my best knowledge and belief.

[Signed] This work are true to my best knowledge and belief.

[Signed] This work are true to my best knowledge and belief. Diameter of well bore below seal \_\_\_\_\_16" in. (Drilling Machine Operator) Drilling Machine Operator's License No. 883 Number of sacks of bentonite used in well seal ..... Brand name of bentonite ..... Water Well Contractor's Certification: Number of pounds of bentonite per 100 gallons This well was drilled under my jurisdiction and this report is ..... Ibs./100 gals. true to the best of my knowledge and belief. Was a drive shoe used? Yes No-Plugs ...... Size: location ...... ft. Name S & M Drilling & Supply Inc.

(Person, firm or corporation) (Type or print) Did any strata contain unusable water? 

Yes No Address 399 S.E. Walnut St., Canby, Or. Type of water? depth of strata

Contractor's License No. 497 Date 7-22, 19.76