NOTICE TO WATER WELL CONTRACTOR

of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON within 30 days from the date of well completion.

WATER WELL REPORT C IVED

State OF OREGON

Please type or print)

Fo not write above this line)

RESOURCES

State

			'· ······	
SMUL	1976		<b>⋨</b> ゃ	/IE-28
30.00	Sta	te Permit	Noシン	///
- necol	IRCES L	EFI.	4	,

	WATER RESOURCE			
(1) OWNER:	(10) LOCATION OF WELL:			
Name Roy A. Lohse	County Clackamas Driller's well number			
Address 9400 S Gribble	570 7.0 433			
Canby, Oregon 97013	/4 DOCUMENT 1. 2 1t.	7. <u>M</u>		
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivision corner			
New Well ★ Deepening				
If abandonment, describe material and procedure in Item 12.				
	(11) WATER LEVEL: Completed well.			
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found _80	£t		
Rotary Driven Domestic X Industrial Municipal Domestic X	Static level 51 ft. below land surface. Date 3-25-	-7		
Dug	Artesian pressure lbs. per square inch. Date			
CASING INSTALLED: Threaded Welded Threaded District Case 250	(12) WELL LOG: Diameter of well below casing 6"  Depth drilled 84 ft. Depth of completed well 82	*		
ft. Gageft.		ft		
PERFORATIONS: Perforated?  Yes  No.	Formation: Describe color, texture, grain size and structure of materia and show thickness and nature of each stratum and aquifer penetrat with at least one entry for each change of formation. Report each change position of Static Water Level and indicate principal water-bearing stra	ted,		
Type of perforator used	MATERIAL From To SWI	 L		
Size of perforations in. by in.	Soil brown 0 2			
perforations fromft. toft.	Clay brown 2 38			
perforations from	Clay sandy brown 38 44			
perforations from ft. to ft.	Gravel prown 44 64			
	Gravel grey 64 80			
(7) SCREENS: Well screen installed?   Yes  No	Gravel (pea) black wb 80 84 51	_		
Manufacturer's Name				
Type Model No.				
Diam. Slot size Set from ft. to ft. to ft.				
(8) WELL TESTS: Drawdown is amount water level is lowered below static level				
Was a pump test made? ☐ Yes ☒ No If yes, by whom?				
Yield: gal./min. with ft. drawdown after hrs.		—		
" " "				
" " " "				
h				
		_		
Artesian flow g.p.m.	A STATE OF THE STA	_		
sperature of water 54 Depth artesian flow encountered ft.	Work started 5-21 19.76 Completed 5-24 19.7	<del>6</del>		
(9) CONSTRUCTION:	Date well drilling machine moved off of well 5-25 19	70		
Well seal—Material usedBentonite	Drilling Machine Operator's Certification:	<u></u> -		
Well sealed from land surface toft.	This well was constructed under my direct supervision.  Materials used and information reported above are two to re-	n.		
Diameter of well bore to bottom of sealin.  Diameter of well bore below sealin.	best knowledge and belief.	•		
	[Signed] Date 5-26 , 19.7	6		
Number of sacks of cement used in well seal sacks  Number of sacks of bentonite used in well seal sacks	Drilling Machine Operator's License No. 776			
Brand name of bentonite	g dated b License 140.			
Number of pounds of bentonite per 100 gallons	Water Well Contractor's Certification:			
of water	This well was drilled under my jurisdiction and this report	is		
Was a drive shoe used? XYes No Plugs Size: location ft.	true to the pest of my knowledge and belief.			
Did any strata contain unusable water? Yes No	Name A C Stites  (Person, firm or corporation) (Type or print)			
Type of water? depth of strata	Address 28290 S. Dryland Rd. Canby, 97913			
Method of sealing strata off	11/1/26			
	[Signed]			
Was well gravel packed? ☐ Yes ☑ No Size of gravel:	(Water Well Contractor)			
Gravel placed fromft. ioft.	Contractor's License No. 522 Date 526 , 19.74	6		
TICH ADDITIONAL COMME		_		