NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the state engineer, Salem, Oregon 97310 within 30 days from the date of well completion.

STATE ENGINEER, SALEM, OREGON 97310 of well completion.

3 1966 STATE OF OREGON (Please type or print) G-4620

State Well No.

State Permit No. .....

-	0 1000	
(1) OWNER: STATE ENGINEER	(11) WELL TESTS: Drawdown is amount to lowered below static let	water level is
Name andrus, Inden.	Was a pump test made test wo If yes, by whom	
Address 207 nw. 3rd	Yield: gal./min. with ft. drawdow	
Canby Oregon.	" "	"
(2) LOCATION OF WELL:	" " "	"
County Clackanas Priller's well number/966- 16	Bailer test 60 gal./min. with 10 ft. drawdo	wn after / hrs.
14 14 Section 28 T.3 S R. / E W.M.	Artesian flow g.p.m. Date	
Bearing and distance from section or subdivision corner	Temperature of water Was a chemical analysis n	nade? Yes No
	(12) WELL LOG: Diameter of well below case	sing
	Depth drilled 190 ft. Depth of completed wel	1 184 ft.
	Formation: Describe by color, character, size of material show thickness of aquifers and the kind and nature of t stratum penetrated, with at least one entry for each ch	and structure, and he material in each
	stratum penetrated, with at least one entry for each ch	lange of formation.
(3) TYPE OF WORK (check):	MATERIAL	FROM TO
	Top soil	03
New Well Deepening Reconditioning Abandon and and and and procedure in Item 12.	Sand Brown medium	3 66
	Chavel + sand	6668
(4) PROPOSED USE (check): (5) TYPE OF WELL:	Dand, brown, med	68 72
Domestic   Industrial   Municipal   Rotary   Driven	gravel + Sand	72 74
rrigation Test Well Other Dug Bored	Thavel, med to large	74 48
(E) CASING INSTALLED.	Sand, mich + Med glavel	78/0/
Threaded Welded	Dand Distun, Medium	101 103
8 "Diam. from 0 ft. to 184 ft. Gage 25	Sand + gravet, the med	105 107
" Diam. fromft. toft. Gage	Iclay blue	10150
	Land Line	150 112
(7) PERFORATIONS: Perforated?  Yes To No	Clay Blue	162 184
Type of perforator used	Sand med (water)	184 189
Size of perforations in. by in.	Clay blue	189 196
perforations from ft. to ft.		
perforations from ft. to ft.		
perforations from ft. to ft.		
perforations fromft. toft.  perforations fromft. toft.		
(8) SCREENS: Well screen installed?  Yes No		
Manufacturer's Name		
Model No.		
Slot size Set from ft. to ft.	Work started 204 /8 19/6 Completed 7716	24.3/ 1966
Diam Slot size Set from ft. to ft.	Date well drilling machine moved off of well 700 6.	3/ 1966
(9) CONSTRUCTION:	(13) PUMP:	
Well seal—Material used in seal Bentonite	Monufacturaria Nama	
Depth of seal	Manufacturer's Name	
Diameter of well bore to bottom of seal		.P
Were any loose strata cemented off? 🗆 Yes 🖟 No Depth	Water Well Contractor's Certification:	
Was a drive shoe used? MYes □ No □ .	This well was drilled under my jurisdiction as	nd this report is
Was well gravel packed? [] Yes No Size of gravel:	true to the best of my knowledge and belief.	4
Gravel placed from ft. to ft.	NAME Skylls Uniling of Su	pply.
Oid any strata contain unusable water?   Yes No	(Person, firm or corporation) (Type or print)	
Type of water? depth of strata	Address Gladstone Orga	
Method of sealing strata off	Drilling Machine Operator's License No. 222	224
(10) WATER LEVELS:		1.
Static level 90 ft. below land surface Date may 3/-	[Signed] (Water Well Contractor)	pee
Artesian pressure lbs. per square inch Date	Contractor's License No. 58 Date May 3	
	Date Date	