ORIGINAL  File Original and Duplicate with the STATE ENGINEER, SALEM, OREGON  ORIGINAL  WATER WI  TATE ORIGINAL  STATE O	ELL REPORTO 9748 State Well No. 3/1.	_ 28L(I)	
STIPLIN, OTTEGON	State Permit No		
(1) OWNER: Name Tom & John R. Dodds	(11) WELL TESTS: Drawdown Earlow at the revel is lowered below static level		
Address 799 N.E. Columbia Blvd.	Was a pump test made? M Yes \( \subseteq \text{No If yes, by whom?} \) Yield: 600 gal/min with 14 st dwardows	7	
Portland 11, Oregon	Yield: 600 gal./min. with 14 ft. drawdown 7 "	A	
(2) LOCATION OF WELL:	" 300 " 5 "	<del></del>	
Claskomas	Bailer test gal./min. with ft. drawdown	after hre	
WE I CW I C I DO TO C T TO	Artesian flow g.p.m. Date		
Bearing and distance from section or subdivision corner	Temperature of water 56 Was a chemical analysis mad	le? 🗆 Yes 📅 No	
Well is located S. O deg.2'W.3535.11 f	(10)		
and N. 89 deg. 18 W. 1012.11 ft. from the		inches	
North quarter Section corner of Section	The state of the s		
28; T.3 S. R.1 E. of W.M. in Clackames	Formation: Describe by color, character, size of material show thickness of aquifers and the kind and nature of the stratum penetrated with at least one active for the stratum penetrated.	and structure, and e material in each	
County, Oregon		inge of formation.	
TYPE OF WORK (check):	Top Soil	FROM TO	
777-17 76	Sandy loam	0 5	
Here well be Deepening ☐ Reconditioning ☐ Abandon ☐ If abandonment, describe material and procedure in Item 11.	Dry gravel & boulders	5 18 18 65	
	Loose gravel (Water)	65 70	
(4) PROPOSED USE (check): (5) TYPE OF WELL:	Boulders	70 73	
estic   Industrial   Municipal   Rotary   Driven	Hard Blue clay	73 95	
gation Test Well   Other   Cable   Jetted   Dug   Bored	Tight Gravel	95 112	
(C) CACING INGUALIED	Gravel (Some Water)	112 118	
(6) CASING INSTALLED: Threaded Welded To Diam. from Top ft. to ft. Gage 31.20#		118 155	
Diam. fromft. toft. Gage OI-2Uff	Gray & Black Sand some Wood		
"Diam. fromft. toft. Gage	(WATER)		
It. to	Blue Clay	160 175	
(7) PERFORATIONS: Perforated? Yes □ No			
Type of perforator used Mills			
SIZE of perforations 3/8 in. by 12 in.			
72 perforations from 65 ft. to 72 ft.  128 perforations from 95 ft. to 117			
11.			
perforations fromft. toft.			
perforations fromft. toft.			
(8) SCREENS: Well screen installed   Yes XNo			
facturer's Name			
Type			
Diam.       Slot size       Set from       ft. to       ft.         Diam.       Slot size       Set from       ft. to       ft.			
Stain. Stot size Set from ft. to ft.	Work started <b>7-30-57</b> 19 . Completed <b>8-2</b>	23-57 19	
CONSTRUCTION:	(13) PUMP:		
Was well gravel packed?   Yes X No Size of gravel:	Manufacturer's Name		
Gravel placed from ft. to ft.	Type: H.P.		
Was a surface seal provided? Yes No To what depth? 20 ft.  Material used in seal— Fuddled clay			
Did any strata contain unusable water?   \[ \subseteq \text{ Yes}  \text{ \text{N}} \text{ Vo} \]	Well Driller's Statement:		
Type of water? Depth of strata	This well was drilled under my jurisdiction and true to the best of my knowledge and belief.	d this report is	
Method of sealing strata off			
	NAME Emil O. Beier (Person, firm, or corporation) (Type		
(10) WATER LEVELS:  Static level 58 ft. below land surface Date 2357	Address 7555 O'Neil Road Salem, Oregon		
Static level 58 ft. below land surface Date 23-57  Artesian pressure lbs. per square inch Date	1 000		
	Driller's well number 367		
[Signed] Date Oug 26, 1957	[Signed] (Well Briller)		
V	License No. 89 Date 8-23-5	<b>7</b> , 19	
(USE ADDITIONAL SH	EETS IF NECESSARY)		