TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the
E ENGINEER, SALEM, OREGON 97310
within 30 days from the date of well completion.

RECEIVED
JUN 14 1966
STATE ENGINEER
OREGON

CLAC
009802

WATER WELL REPORT
STATE OF OREGON
(Please type or print)

State Well No. 3/1-30
State Permit No. G-334

(1) OWNER:
Name Charles Cheelds
Address 1560 Sallal Rd. Woodburn

(2) LOCATION OF WELL:
County Clackamas Driller's well number
¼ ¼ Section T. R. W.M.
Bearing and distance from section or subdivision corner
Sec 30 T3S R1E

(3) TYPE OF WORK (check):
New Well ☒ Deepening ☐ Reconditioning ☐ Abandon ☐
[redacted]donment, describe material and procedure in Item 12.

(4) PROPOSED USE (check):
Domestic ☐ Industrial ☐ Municipal ☐
Irrigation ☒ Test Well ☐ Other ☐

(5) TYPE OF WELL:
Rotary ☐ Driven ☐
Cable ☒ Jetted ☐
Dug ☐ Bored ☐

(6) CASING INSTALLED: Threaded ☐ Welded ☒
10" Diam. from +1 ft. to 140 ft. Gage ¼
18" Diam. from +8" ft. to 26 ft. Gage ¼
" Diam. from ft. to ft. Gage

(7) PERFORATIONS: Perforated? ☒ Yes ☐ No
Type of perforator used torch
Size of perforations ¼ in. by 4 in.
480 perforations from 80 ft. to 140 ft.
perforations from ft. to ft.
perforations from ft. to ft.
[redacted] perforations from ft. to ft.
perforations from ft. to ft.

(8) SCREENS: Well screen installed? ☐ Yes ☒ No
Manufacturer's Name
Type Model No.
[redacted] Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(9) CONSTRUCTION:
Well seal—Material used in seal Bentonite
Depth of seal 24 ft. Was a packer used? no
Diameter of well bore to bottom of seal 24 in.
Were any loose strata cemented off? ☐ Yes ☐ No Depth
Was a drive shoe used? ☐ Yes ☒ No
Was well gravel packed? ☒ Yes ☐ No Size of gravel:
Gravel placed from 26 ft. to 140 ft.
Did any strata contain unusuable water? ☐ Yes ☒ No
Type of water? depth of strata
Method of sealing strata off

(10) WATER LEVELS:
Static level 70 ft. below land surface Date 6/9/66
Ar[redacted] pressure lbs. per square inch Date

(11) WELL TESTS: Drawdown is amount water level is lowered below static level
Was a pump test made? ☒ Yes ☐ No If yes, by whom?
Yield: 200 gal./min. with 22 ft. drawdown after 5 hrs.
" " "
" " "
Bailer test gal./min. with ft. drawdown after hrs.
Artesian flow g.p.m. Date
Temperature of water 53 Was a chemical analysis made? ☐ Yes ☒ No

(12) WELL LOG: Diameter of well below casing —
Depth drilled 140 ft. Depth of completed well 140 ft.
Formation: *Describe by color, character, size of material and structure, and show thickness of aquifers and the kind and nature of the material in each stratum penetrated, with at least one entry for each change of formation.*

MATERIAL	FROM	TO
Top Soil	0	2
Brown Clay	2	46
Sand brown Clay	46	73
fine Brown Sand	73	105
Course Brown Sand	105	136
Brown + blue Clay	136	138
4" gravel	138	140

Work started 5/28 1966 Completed 6/9 1966
Date well drilling machine moved off of well 6/9 1966

(13) PUMP:
Manufacturer's Name
Type: H.P.

Water Well Contractor's Certification:
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
NAME Parrow Drilling & Supplies (Person, firm or corporation) (Type or print)
Address 729 N. McKinzie Newberg
Drilling Machine Operator's License No. 82
[Signed] Charles M. Parrow (Water Well Contractor)
Contractor's License No. 117 Date 6/10, 1966

(USE ADDITIONAL SHEETS IF NECESSARY)