## STATE OF OREGON

## RECEIVED

WATER WELL REPORT (as required by ORS 537.765)

APR 3 1986 EASE TYPE or PRINT IN INK



WATER RECURCES DEPT	(for official use only)
(1) OWNER: SALEM, GREGON	(10) LOCATION OF WELL by legal description:
Name Gordon Smith	County Clatsup N44 SE 4 of Section 25 of Township 5N Range 8 W WM.
Address Elsie Rt. Box 195	Township (Township is North or South), Range (Range is East or West), WM.
City Seaside State Oregon	(Township is North or South) (Range is East or West)
(2) TYPE OF WORK (check):	Tax Lot Lot Block Subdivision MAILING ADDRESS OF WELL (or nearest address) SAME
New Well Deepening  Reconditioning  Abandon	
If abandonment, describe material and procedure in Item 12.	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	(11) WATER LEVEL of COMPLETED WELL:
Rotary Air Driven Domestic Industrial Municipal D	Depth at which water was first found 15 ft.
Rotary Mud Dug Irrigation Withdrawal Reinjection	Static level 14 ft. below land surface. Date 3-10-86
Other: Piezometric  Grounding  Test	Artesian pressure lbs. per square inch. Date
CA CITY CITY CITY CITY CITY CITY CITY CITY	(12) WELL LOG: Diameter of well below casing
(5) CASING INSTALLED: Steel K Plastic Threaded Welded K	Depth drilled //5 ft. Depth of completed well //5 ft.
6 Diam from 1 1 ft to 38 ft. Gauge 250	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of
"Diam. fromft. toft. Gauge	formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.
LINER INSTALLED: Steel   Plastic	water-bearing strata.
Threaded Welded	MATERIAL From To SWL
4. Diam. from 2.5. ft. to 115 ft. Gauge PVC 160	Top soil
(6) PERFORATIONS: Perforated? MY Yes I No	Clay (Brown) + Coarse Grave / 21/4
Size of perforations 3/8 in. by Round in.	Gray Clay stone + Coarse Grave   21 31
360 perforations from 25 ft. to ft.	Gray Claystone 31 76 Gray Claystone + Med. Gravel 76 115 14
perforations from ft. to ft.	Way Claystone + Med. Gravel 76 115 14
perforations from ft. to ft.	- CHAILET DEELTING
(7) SCREENS: Well screen installed?   Yes No	
Manufacturer's Name	the first section of the section of
TypeModel No	1 7.0
Diam. Slot Size Strom ft. to ft.	
Diam Slot Size Set from ft. to ft.	AT
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	
Was a pump test made?   Yes  No If yes, by whom?	
d: gal./min. with ft. drawdown after hrs.	
Air test 20 gal./min. with drill stem at 100 ft. 1 hrs.	
Bailer test gal./min. with ft. drawdown after hrs,	
Artesian flow g.p.m.	
perature of water 5 4 Depth artesian flow encountered ft.	
9) CONSTRUCTION: Special standards: Yes \( \text{No } \)	Date work started 3-9-86 /completed 3-9-86
Well seal—Material used Partland Cement	Date well drilling machine moved off of well  10 Mar. 1986
Well sealed from land surface to	(unbonded) Water Well Constructor Certification (if applicable):
Diameter of well bore to bottom of seal in.	This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
Diameter of well bore below sealin.  Amount of sealing materialsacks pounds □	_
How was cement grout placed? Pumped.	[Signed]
who couldn't grow pieces.	(bonded) Water Well Constructor Certification:
3 - 27 - 27	Bond 801024 Issued by Data + Staff Service Co. (Surety Company Name)
Vas pump installed?	On behalf of Larry Every Well Drilling Inc
Vas a drive shoe used? 🕱 Yes 🗆 No Plugs Size: location ft.	(type or p int name of Water Well Constructor)
Did any strata contain unusable water?    Yes  No	This well was drilled under my jurisdiction and this report is true to the
'ype of Water? depth of strata	best of my knowledge and belief:
Method of sealing strata off	(Signed) (Water Well Constructor)
Vas well gravel packed?  Yes No Size of gravel:	(Dated)3-10-86
ravel placed from ft. to ft.	
NOTICE TO WATER WELL CONSTRUCTOR	WATED DECOMPORED DEDADENING