NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report
are to be filed with the

WATER RESOURCES DEPARTMENT SALEM, OREGON 97310 within 30 days from 1 within 30 days from the date of well completion.

WATER WELL REPORT

STATE OF OREGON

(Please type or print) (Do not write above this line)

State Well No. 7N/10W-9dc
State Permit No.

1) OWNER:	10) LOCATION OF WELL:		
Neacoxi Mobile Home Park	County Clatsop Driller's well number		
Marrenton, Oregon 97146	SW 1/4 SE 1/4 Section 9 T. 7 NR. 10 W. W.M.		
11.00 - 140 - 121 - 1	Bearing and distance from section or subdivision corner		
2) TYPE OF WORK (check):			
New Well Deepening Reconditioning Abandon Reconditioning Abandon		**	
f abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.		
3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 65 ft.		
Rotary L Driven Domestic L Industrial Municipal L	Static level 2 ft. below land su	$_{\text{trface. Date}}$ 8/4/79	
Cable	Artesian pressure lbs. per square inch. Date		
CASING INSTALLED: Threaded Welded X .250 .250	(12) WELL LOG: Diameter of well below casing ————————————————————————————————————		
Type of perforator used	MATERIAL	From To SWL	
Size of perforations in. by in.	Fine gray sand	0 3	
perforations fromft. toft.	Muddy gray-brown sand w/wood		
perforations fromft. toft.	& clay streaks	3 38	
perforations fromft. toft.	Fine brown sand w/occ.brown	00 50	
	clay seams	38 53	
(7) SCREENS: Well screen installed? A Yes \(\subseteq \) No	Soft dark gray sandy clay	53 65	
Manufacturer's Name UOP Johnson	Fine to med. gray sand w/wood	65 82	
Type Irrigator Model No. Diam 5-9/16 Slot size .20 Set from 65 ft. to 75 ft.	& shells	82 85	
Diam Slot size Set from ft. to ft.	Firm gray sandy shale	-02 00	
Diam. Slot size Set from It. to	WELL COMPLETED TO 80'		
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	05050465		
Was a pump test made? ☐ Yes 🏧 No If yes, by whom?	REGEIVEU =		
40	0.115.0		
Yield: 60 gal./min. with 40 ft. drawdown after 75 nrs.	AUG9 - 1979		
100 60 11	WATER RESOURCES DEPT		
	SALEM, OREGON		
Bailer test gal./min. with ft. drawdown after hrs.			
Artesian flow g.p.m.		0/5/50	
perature of water Depth artesian flow encountered ft.	Work started 8/4/79 19 Complete		
(9) CONSTRUCTION:	Date well drilling machine moved off of well	8/5/79 19	
Well seal—Material used Cement Well sealed from land surface to 50 ft. Diameter of well bore to bottom of seal 10 in. Diameter of well bore below seal 10 in. Number of sacks of cement used in well seal 10 sacks How was cement grout placed? Tremied into annular bore back to ground level.	Drilling Machine Operator's Certification: This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief. [Signed] Date 8/6/79, 19 Drilling Machine Operator's License No. This well was drilled under my jurisdiction and this report is		
Was a drive shoe used? ☐ Yes 🍇 No Plugs Size: location ft.	true to the best of my knowledge and bel Name A.M.JANNSEN WELL DRILLING	ief.	
Did any strata contain unusable water? Yes No Type of water? depth of strata	(Person, firm or corporation) (Type or print) Address 21075 SW Tualatin Valley Hwy. Aloha, Or.		
Method of sealing strata off	Isimal The Only	MASI	
Was well gravel packed? Yes □ No Size of gravel: 20 mil	[Signed] (Water Well Contr		
Gravel placed from 50 ft, to 80 ft.	Contractor's License No. 79 Date	8/6/79 ₁₉	
	DEETS IF NECESSARY)	SP*45656-	