STATE OF OREGON

RECEIVED

WATER WELL REPORT (as required by ORS 537.765)

JAN 1 3 1986 PLEASE TYPE OF PRINT IN INK

WATER RESOURCES DEDT (for official use only) ealen, oregon (10) LOCATION OF WELL by legal description: (1) OWNER: Leo Deal Columbia SE 14 NE 14 of Section 19 Name 74549 Deal Road 2 W Address Township _ (Range is East or West) (Township is North or South) Rainier. City State Ore. Lot_ (2) TYPE OF WORK (check): MAILING ADDRESS OF WELL (or nearest address) 74866 Doan Road New Well Reconditioning Deepening Abandon 🗌 Rainier. Ore If abandonment, describe material and procedure in Item 12. (11) WATER LEVEL of COMPLETED WELL: (3) TYPE OF WELL: (4) PROPOSED USE (check): Depth at which water was first found Rotary Air 45 Industrial Driven ☐ Municipal Thermal: ft. below land surface. Date 1-03-86 Static level Rotary Mud Dug Withdrawal ☐ Reinjection Trrigation Artesian pressure lbs. per square inch. Date Other Piezometric ☐ Grounding Bored (12) WELL LOG: Diameter of well below casing .. (5) CASING INSTALLED: Steel Depth drilled 36. ft. Depth of completed well ft. apx Plastic Threaded Welded Formation: Describe color, texture, grain size and structure of materials; and show thickness 6 " Diam. from +2" ... ft. to ... 29! 4!! ft. and nature of each stratum and aquifer penetrated, with at least one entry for each change of Gauge formation. Report each change in position of Static Water Level and indicate principal" Diam. from ft to ft Gauge water-bearing strata. LINER INSTALLED: MATERIAL From То SWL Threaded Welded Broken rock black Ω Gauge Rock black hard 3 78 (6) PERFORATIONS: ☑ No Perforated?

Yes Rock blue soft 78 89 Size of perforations in. Rock gray soft 89 216 perforations from ft. to ft. Rock blue medium 216 271 perforations from ft. to Rock blue-green med.-soft 271 301 perforations from ft. to ft. Rock grayish-brown med.-soft <u> 307</u> 301 Clay yellow hard (7) SCREENS: 307 316 Well screen installed? ☐ Yes ☑ No Shale blue and claystone blue 316 321 Manufacturer's Name some caving Shale and clay red 321 330 Diam. Slot Size Set from ft. to ft. Clay stone blue-green caving Slot Size Set from ft. to ft. 361 Drawdown is amount water level is lowered (8) WELL TESTS: below static level Was a pump test made?

Yes

No If yes, by whom? gal./min. with ft. drawdown after hrs. Air test gal./min. with drill stem at 330 ft. hrs. Bailer test gal./min. with ft. drawdown after Artesian flow g.p.m. pperature of water Depth artesian flow encountered Date work started ___ /completed_ (9) CONSTRUCTION: Special standards: Yes I No IX 1-03-86 Date well drilling machine moved off of well Well seal—Material used cement grout (unbonded) Water Well Constructor Certification (if applicable): Well sealed from land surface to .. This well was constructed under my direct supervision. Materials used and 10 in. Diameter of well bore to bottom of seal information reported above are true to my best knowledge and belief. Amount of sealing material With 5 % bent. 10 sacks XI pounds I How was cement grout placed? DUMDED in with tremmie pipe. (bonded) Water Well Constructor Certification: Bond #471F1529 Issued by: Travelers Insurance (number) (Surety Company Name) On behalf of Dale McGhee & Sons Well Drilling Inc (type or print name of Water Well Constructor) Was pump installed? Was a drive shoe used? Yes No Plugs Size: location ft. ☐ Yes ☒ No Did any strata contain unusable water? This well was drilled under my jurisdiction and this report is true to the Type of Water? best of my knowledge and belief: depth of strata Method of sealing strata off (Signed) Was well gravel packed?

Yes No (Dated) January 07, 1986

Gravel placed from ...