NOTICE TO WATER WELL CONTRACTOR TO THE ORIGINAL AND STATE OF THE ORIGINAL AND STATE ORIGINAL AND STATE OF THE ORIGINAL AND

STATE ENGINEER, SALEM, OREGON #310 E ENGINE FLOOR print)
within 30 days from the date SALEM ORE (Do not write 5) ve this line)

CCOLUSTATE Well No. 7N/2W-26

State Permit No.

(1) OWNER:	(10) LOCATION OF WELL:	-	
Name Bob Gibson	County Columbia Driller's well nu	mber /	
Address Stop NN TAVERN	1/4 1/4 Section 26 T. 7N	R. 2 W.M.	
KAINIER, DREGON	Bearing and distance from section or subdivision		
(2) TYPE OF WORK (check):			
New Well ☐ Deepening ☐ Reconditioning ☐ Abandon ☐	<u> </u>		
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.		
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 243 ft.		
Rotary Driven Domestic Industrial Municipal Domestic	Static level 362 ft. below land so	urface. Date 2 - 4 - 74	
Dug   Bored   Irrigation   Test Well   Other	Artesian pressure lbs. per square		
CASING INSTALLED: Threaded Welded			
6 "Diam. from O ft. to 4/8" ft. Gage 250	(12) WELL LOG: Diameter of well below casing		
5 " Diam. from 35 7" ft. to 508 ft. Gage 12	Depth drilled 508 ft. Depth of completed well 508 ft.		
	Formation: Describe color, texture, grain size a and show thickness and nature of each stratum		
	with at least one entry for each change of format	ion. Report each change in	
PERFORATIONS: Perforated? Yes No.	position of Static Water Level and indicate princ	ipal water-bearing strata.	
Type of perforator used Torch cut	MATERIAL	From To SWL	
Size of perforations 3/8 in. by 10 in.	Louiders	9/3	
56 perforations from 368 ft. to 508 ft.	JARK CIAY BROWN	3 18	
ft. toft.	ROCK Med, hARd hASAH CRIMIL	18 36 36 58 48 75	
perforations fromft. toft.	ROCK BURCK BASAIT MED	75 80	
	BOCK CRUMble colored &	90 162	
(7) SCREENS: Well screen installed?   Yes   No	Pock black soft	128 195	
Manufacturer's Name	ROCK black SOFT	3/4 2/2	
Type Model No.	ROCK BIACK MED	332 237	
Diam Slot size Set from ft. to ft.	20 FK 8/ACK Med	337 358	
Diam	ROCK BIACK Med	290 390	
	ROCK BIRCK Med.	297 312	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	POCK BACK MARC	334 339	
Was a pump test made? Yes No If yes, by whom?	ROCK black SOFT	339 370	
Yield: 6 70 gal./min. with 365 ft. drawdown after / hrs.	ROCK colored CRUMbly 50FA	370 375	
FIR ROTORY test At som Feet "	ROCK BLACK SOFT	375 377	
" " " " "	ROCK black hard	377 387	
	- ROCK black medium	387 472	
Bailer test gal./min. with ft. drawdown after hrs.	Rock Red medium	472 496	
Artesian flow g.p.m.	ROCK black medium	496 508	
erature of water Depth artesian flow encountered ft.	Work started /- 29 1974 Completed	12-4 1974	
(9) CONSTRUCTION:	Date well drilling machine moved off of well	2-5 1974	
Well seal-Material used CEMENT - GROUT	Drilling Machine Operator's Certification:	•	
Well sealed from land surface toft.	This well was constructed under my direct supervision.		
Diameter of well bore to bottom of seal	Materials used and information reported above are true to my best knowledge and belief.		
Diameter of well bore below seal	[Signed] Dale Mc Bhu Date 2-12 1974		
Number of sacks of cement used in well sealsacks	(Drilling Machine Operator)		
Number of sacks of bentonite used in well seal sacks	Drilling Machine Operator's License No	363	
Brand name of bentonite			
Number of pounds of bentonite per 100 gallons	Water Well Contractor's Certification:		
of water lbs./100 gals.	This well was drilled under my jurisdic true to the best of my knowledge and belie	tion and this report is	
Was a drive shoe used? 🗗 Yes 🗌 No Plugs Size: location ft,_	In Della IVI I I an I I'm I De I I ac-		
Did any strata contain unusable water? 🗌 Yes 🖟 No	(Person, firm or corporation)	(Type or print)	
Type of water? depth of strata	Address 3032 Allen St.	Kelso, Wash	
Method of sealing strata off	[Signed] Dale Mc Dhy	e e e e e e e e e e e e e e e e e e e	
Was well gravel packed? [] Yes [] No Size of gravel:	(Water Well Contract	ctor)	
Gravel placed from	Contractor's License No. 494 Date 9	- 12 10/4	
		+ D	