NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310 within 30 days from the date of well completion.

RECEIVED MAY 9 1985 WATER RESOURCES DEPT SALEM, OREGON

WATER WELL REPORT
STATE OF OREGON
(Please type or print)
(Do not write above this line)

COLU 2615

State Well No. 8N/3W-33
State Permit No.

(1) OWNER:
Name Jerry Couture
Address 24491 Vanswell Rd.
Rainier, Oregon. 97048

(2) TYPE OF WORK (check):
New Well ☒ Deepening ☐ Reconditioning ☐ Abandon ☐
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:
Rotary ☒ Driven ☐
Cable ☐ Jetted ☐
Dug ☐ Bored ☐

(4) PROPOSED USE (check):
Domestic ☒ Industrial ☐ Municipal ☐
Irrigation ☐ Test Well ☐ Other ☐

(5) CASING INSTALLED: Threaded ☐ Welded ☒
6" Diam. from +1 ft. to 75 ft. Gage 250
4½" Diam. from 70 ft. to 483 ft. Gage SDR26
PVC Diam. from ft. to ft. Gage

(6) PERFORATIONS: Perforated? ☒ Yes ☐ No.
Type of perforator used Drilled
Size of perforations ½ in. by Round in.
50 perforations from 453 ft. to 483 ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS: Well screen installed? ☐ Yes ☒ No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS: Drawdown is amount water level is lowered below static level
Was a pump test made? ☐ Yes ☒ No If yes, by whom?
Yield: gal./min. with ft. drawdown after hrs.
" " " "
" " " "
Bailer test 15 gal./min. with 80 ft. drawdown after 1 hrs.
Artesian flow g.p.m.
Temperature of water Depth artesian flow encountered ft.

(9) CONSTRUCTION:
Well seal—Material used Cement
Well sealed from land surface to 75 ft.
Diameter of well bore to bottom of seal 10" in.
Diameter of well bore below seal 6 in.
Number of sacks of cement used in well seal 18 sacks
How was cement grout placed? Pressure Pumped
Was a drive shoe used? ☒ Yes ☐ No Plugs Size: location ft.
Did any strata contain unusable water? ☐ Yes ☒ No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? ☐ Yes ☒ No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:
County Columbia Driller's well number
¼ ¼ Section 33 T. 8 R. 3 W. W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.
Depth at which water was first found 450 ft.
Static level 397 ft. below land surface. Date 4/30/85
Artesian pressure lbs. per square inch. Date

(12) WELL LOG: Diameter of well below casing 6"
Depth drilled 483 ft. Depth of completed well 483 ft.
Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
Clay, Yellow	0	8	
Clay, Red	8	16	
Clay, Gray	16	25	
Clay, Yellow	25	52	
Shale, Blue	52	68	
Rock, Blue Broken	68	70	
Rock, Blue Basalt, Hard	70	120	
Shale, Yellow	120	129	
Rock, Blue Med	129	292	
Rock Brown Med	292	315	
Rock, Blue Med.	315	450	
Rock Blue Broken Water Bearing	450	468	
Rock, Blue Basalt	468	483	

Work started 4/24 1985 Completed 4/30 1985
Date well drilling machine moved off of well 4/30 1985

Drilling Machine Operator's Certification:
This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] [signature] Date 5/7, 1985
(Drilling Machine Operator)
Drilling Machine Operator's License No. WWC 589

Water Well Contractor's Certification:
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name Williams Well Drilling Inc.
(Person, firm or corporation) (Type or print)
Address 957 Jackson Hwy. S. Toledo, Wash.
[Signed] [signature]
(Water Well Contractor)
Contractor's License No. 589 Date 5/7, 1985

(USE ADDITIONAL SHEETS IF NECESSARY)

SP*45656-119