

NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the

WATER WELL REPORT

RECEIVED

3564
14W-288

STATE ENGINEER, SALEM, OREGON 97310
within 30 days from the date of well completion.

STATE OF OREGON
(Please type or print)

NOV 2 1976

State Well No.

State Permit No.

COLU 2639

(1) OWNER:

Name Quincey Water Association
Address P.O. Box 403
Clatskanie, Oregon

(2) TYPE OF WORK (check):

New Well [X] Deepening [] Reconditioning [] Abandon []
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary [X] Driven []
Cable [] Jetted []
Dug [] Bored []

(4) PROPOSED USE (check):

Domestic [] Industrial [] Municipal []
Irrigation [] Test Well [X] Other []

CASING INSTALLED:

6" Diam. from 1.2 ft. to 112.7 ft. Gage 250
5" Diam. from 10.6 ft. to 20.6 ft. Gage 188

PERFORATIONS:

Perforated? [X] Yes [] No.
Type of perforator used torch cut
Size of perforations 3/8 in. by 6 in.
78 perforations from 12.1 ft. to 20.6 ft.

(7) SCREENS:

Well screen installed? [] Yes [X] No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level
Was a pump test made? [X] Yes [] No If yes, by whom? Driller
Yield: 30 gal./min. with 129 ft. drawdown after 1 hrs.
1" Rotary tested at 20.5 Feet
Baller test gal./min. with ft. drawdown after hrs.
Artesian flow g.p.m.
Temperature of water Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Well seal-Material used cement
Well sealed from land surface to 27 ft.
Diameter of well bore to bottom of seal 10 in.
Diameter of well bore below seal 6 in.
Number of sacks of cement used in well seal 11 sacks
Number of sacks of bentonite used in well seal sacks
Brand name of bentonite
Number of pounds of bentonite per 100 gallons of water lbs./100 gals.
Was a drive shoe used? [X] Yes [] No Plugs Size: location ft.
Did any strata contain unusable water? [X] Yes [] No
Type of water SOFT SANDY CLAY depth of strata 74-91
Method of sealing strata off Driving CASING
Was well gravel packed? [] Yes [X] No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County Columbia Driller's well number
1/4 1/4 Section 26 T. 8N R. 4 W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found 108 ft.
Static level 76 ft. below land surface. Date 10-20-76
Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing 0
Depth drilled 206 ft. Depth of completed well 206 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

Table with columns: MATERIAL, From, To, SWL. Entries include top soil, clay brown, sandstone blue soft, etc.

Work started Oct 15 1976 Completed Oct. 20 1976
Date well drilling machine moved off of well Oct 21 1976

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] Dale McRhee Date 10-30, 1976

Drilling Machine Operator's License No. 363

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name Dale McRhee Well Drilling

Address 3032 Allen St. Astoria, OR
[Signed] Dale McRhee

Contractor's License No. 424 Date 10-30, 1976