NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

WATER WELL REPORT

STATE OF OREGON

State	Well	No.	٥	11	IW	 7

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

(Please type or print) (Do not write above this line)

State Permit No.

(1) OWNER:	(10) LOCATION OF WELL:				
Name RUDDS TRAILER COURT	County ()LUMBIA Driller's well number 5/2				
Address RT 2 Boy 316 B #9B	1/4 1/4 Section 7 T. 3 N R. / W.M.				
SCAPPOOSE OREGON	Bearing and distance from section or subdivision corner				
(2) TYPE OF WORK (check):					
New Well Deepening □ Reconditioning □ Abandon □					
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.				
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 18 ft.				
Determine D	0 - 12/14/-				
Cable Domestic Industrial Industrial					
Dug Bored Irrigation Test Well Other	Artesian pressure lbs. per square inch. Date				
CASING INSTALLED: Threaded Welded	(12) WELL LOG: Diameter of well below casing				
"Diam. from + 1 ft. to 62 ft. Gage .250"	76				
"Diam. from ft. to ft. Gage ft. Gage					
	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated,				
	with at least one entry for each change of formation. Report each change in				
PERFORATIONS: Perforated? Yes No.	position of Static Water Level and indicate principal water-bearing strata.				
Type of perforator used	MATERIAL From To SWL				
Size of perforations in. by in.	TOP SOIL				
perforations from ft. to ft.	BROWN CLAY 1 4				
perforations from ft. to ft.	CEMBUTED (TRAVEL 4 19				
perforations from ft. to ft.	BLUE CLAY, 19 29				
	CEMENTED GRAVEL 29 37				
(7) SCREENS: Well screen installed? X Yes No	LOOSE GRAVEL 39 63				
Manufacturer's Name JOHNSON	COARSE SAND 63 66 8				
TypeModel No.	WATER BEARING				
Diam. Slot size Set from ft. to ft.	LOOSE SAND AND				
Diam. 5 Slot size 20 Set from 62 ft. to 61 ft.	GRAVEL 66 7.3 8				
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	WATER BEARING)				
lowered below static level	FINE SAND SOME				
Was a pump test made? ☐ Yes No If yes, by whom?	GRAVEL 7.3 75				
Yield: gal./min. with ft. drawdown after hrs.	RECEIVED -				
" " " " " " " " " " " " " " " " " " "	DEC271976				
" " "	DECIGO DEDT				
Bailer test 50 gal./min. with 33 ft. drawdown after 1 hrs.	WATER RESOURCES DEPT				
Artesian flow g.p.m.	SALEM, OREGON				
Temperature of water Depth artesian flow encountered	Work started 12/7 1976 Completed 12/14 197				
Temperature of water Deput arcestar now excountered	Date well drilling machine moved off of well 12/14 19 76				
(9) CONSTRUCTION:					
Well seal-Material used	Drilling Machine Operator's Certification:				
Well sealed from land surface to	This well was constructed under my direct supervision Materials used and information reported above are true to m				
Diameter of well bore to bottom of seal,	best knowledge and belief.				
Diameter of well bore below seal in.	[Signed] Date /// , 19./				
Number of sacks of cement used in well sealsacks	Drilling Machine Operator's License No. 329				
Number of sacks of bentonite used in well seal sacks	Diffing Wathing Operator's Diceine No.				
Brand name of bentonite	Water Well Contractor's Certification:				
Number of pounds of bentonite per 100 gallons	This well was drilled under my jurisdiction and this report is				
of waterlbs./100 gals.	true to the best of my knowledge and belief.				
Was a drive shoe used? Yes No Plugs Size: location ft.	Name KELER WELL KILLING LO.				
Did any strata contain unusable water? Yes No	Address 6350 SE BROWNLEE MILWAUKIE				
Type of water? depth of strata	Address 6350 SE DROWNLEE MILWAUKIE				
Method of sealing strata off	[Signed]				
Was well gravel packed? ☐ Yes 💆 No Size of gravel:	(Water Well Contractor)				
Gravel placed from ft. to ft.	Contractor's License No. 464 Date 12/19 , 19/				