WATER WELL REPORT

STATE OF OREGON

SEP 14 1981

RECEIVED

WATER RESOURCES DEPT SALEM, OREGON

State Permit No.

(1) OWNER:	(10) LOCATION OF WELL:
Name Fred Bernet	County Columbia Driller's well number 3
Address Route 3 Box 137	4 4 Section 19 T. 3N R. 2W W.M.
City SCAPPOOSE State Chargon	Tax Lot # Lot Blk Subdivision
(2) TYPE OF WORK (check):	Address at well location: Joure 3 Box 141W
New Well	DIKE Kd. SCAPROOSE, OREGON 97050
if abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
	Depth at which water was first found \$20 ft.,
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Static level 9 ft. below land surface. Date 8-2/- 8
Rotary Air Driven Domestic Industrial Municipal Driven Irrigation Test Well Other	Artesian pressure O lbs. per square inch. Date 8-3/-8/
☐ Bored ☐ Thermal: Withdrawal ☐ Reinjection ☐	(12) WELL LOG: Diameter of well below casing
(5) CASING INSTALLED: Steel Plastic	Depth drilled ft. Depth of completed well ft.
Threaded Wolded Wolded	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry
6 "Diam from + 3 ft to 178 6 ft Gauge 250	for each change of formation. Report each change in position of Static Water Level
" Diam. from ft. to ft. Gauge	and indicate principal water-bearing strata.
LINER INSTALLED:	MATERIAL From To SWL
	top soil 02
(6) PERFORATIONS: Perforated? □ Yes □ 16	CYAY BROWN 25
Type of perforator used	31/74 C/A4 6/40 grey 5 59
Size of perforations in. by in.	C/Ay blue giry 59 75
perforations fromft. toft.	3AXdy SIST blue 75 101
perforations from ft. to ft.	SANO AND GLAVE 10/110
perforations from	good water bearing 110 179'9"
	SHNd AND GLAVEL
(7) SCREENS: Well screen installed? Yes Yes	
Manufacturer's Name	
Type Model No.	
Diam. Slot Size Set from ft. to ft.	
Diam. Slot Size Set from ft. to ft. Drawdown is amount water level is lowered	
(8) WELL TESTS: below static level	
a pump test made? Yes No If yes, by whom?	
ried: gal./min. with ft. drawdown after hrs.	
" " "	
Air test 60 gal./min. with drill stem at 198 ft. / hrs.	
Bailer test gal./min. with ft. drawdown after hrs.	
sian flow g.p.m.	
Comperature of water Depth artesian flow encountered ft.	Work started Aug 20 198/ Completed Aug 2/ 198/
(9) CONSTRUCTION: Special standards: Yes No	Date well drilling machine moved off of well #49115+ 21 198/
Well seal—Material used CRM CNT GLOUT	Drilling Machine Operator's Certification:
Well sealed from land surface to 93 ft.	This well was constructed under my direct supervision. Materials used
Diameter of well bore to bottom of seal	and information reported above are true to my best knowledge and belief.
Diameter of well bore below seal	[Signed] Date 9-9, 198
Number of sacks of cement used in well seal sacks	Drilling Machine Operator's License No. 849
How was cement grout placed? THEM MIC G! FE	
	Water Well Contractor's Certification:
W - 12 20 MO -	This well was drilled under my jurisdiction and this report is true to the best offmy knowledge and belief.
Was pump installed? Type HP Depth ft.	Name LARE ME Gree 4-SONS Well Dailling INC
Was a drive shoe used? ☐ Yes ☐ No Plugs Size: location ft. Did any strata contain unusable water? ☐ Yes ☐ No	(Person, firm or corporation) (Type or prifit)
Type of Water? SURFACP depth of strata	Address 32 H/LEN ST. Stey So WASh
Method of sealing strata off CEMENT & CASED	[Signed] Dale Mc Shu
Was well gravel packed? ☐ Yes ☑ No Size of gravel:	(Water Well Contractor)
Gravel placed from	Contractor's License No. 19. 4. Date 52/1. 9. 198