NOTICE TO WATER WELL CONTRACTOR The original and first copy of this per CE | VEALER WELL REPORT are to be filed with the

C 1070 STATE OF OREGON WATER RESOURCES DEPARTMENT APR

within 30 days from the date

State Well No. 3N/2w-22

LLEM, OREGON 97310 APK 0 1979 (Please type or print)	A. Main &	<i>*</i>
nin 30 days from the date of well completion. WATER RESOURCES not write above this line)	2171	State Permit No.
CALEM OREGON	51 m	

DALEM, VALUE	
(1) OWNER:	(10) LOCATION OF WELL:
Name J. Richard Recht	County Columbia Driller's well number
Address 155 Bovet Road	34 34 Section 22, T. 3N R. 2W W.M.
San Mateo, California 94402	Bearing and distance from section or subdivision corner
(2) TYPE OF WORK (check):	
New Well ( Deepening Reconditioning Abandon   If abandonment, describe material and procedure in Item 12.	
	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 235 ft.
Cable	Static level 55,3 ft. below land surface. Date 3-26-79
Oug   Bored   Irrigation   Test Well   Other	Artesian pressure O lbs. per square inch. Date 3-26-79
CASING INSTALLED: Threaded Welded To Sold to Sold ft. to 303'5" ft. Gage 250	(12) WELL LOG: Diameter of well below casing
"Diam. from ft. to ft. Gage	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in
PERFORATIONS:  Perforated? Yes \( \sigma \) No.	position of Static Water Level and indicate principal water-bearing strata.
Type of perforator used Mills Knite  Size of perforations 1/4 in. by 3/8 in.	MATERIAL From To SWL
Size of perforations 179 in. by 3/8 in.  17 perforations from 280 ft. to 302 ft.	Top Soil 0 2 21
perforations from 9,29 ft. to 600 ft.	Class Red Hand 21 28
perforations fromft. toft.	Clad Light Brown 28 39
(E) CODERNO	Clau Blile 39 44
(7) SCREENS: Well screen installed?  West No.	Clay Brown 47 69
Manufacturer's Name	Clay 6-74 69 74
Diam. Slot size Set from ft. to ft.	Clay Gray Dark 74 185 Sund Hone Soft Blue Gray 185 294
Diam Slot size Set from ft. to ft.	Shale Soft 302
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	Sandstone, Soft 302 509
Was a pump test made? Yes   No If yes, by whom	
Yield: 512 gal./min. with 245.7ft. drawdown after 34 hrs.	
or rolary tested at 301 teet. "	
,, U ,, ,, ,, ,, ,, ,, ,, ,, ,, ,, ,, ,,	
Bailer test gal./min. with ft. drawdown after hrs.	
Artesian flow g.p.m.	
perature of water Depth artesian flow encountered ft.	Work started 3-21 1979 Completed 3-26 1979
(9) CONSTRUCTION:	Date well drilling machine moved off of well 3-26 1979
Well seal—Material used Cement Srout	Drilling Machine Operator's Certification:
Well sealed from land surface to	This well was constructed under my direct supervision.  Materials used and information reported above are true to my
Diameter of well bore to bottom of seal 10" to 41' in. 8"to 230	best knowledge and belief.
Diameter of well bore below seal in.	[Signed] Jale McLine Operator) Date
Number of sacks of cement used in well seal sacks  Now was cement grout placed? by "Pipe and "  OWILL OUM O	Drilling Machine Operator's License No. 343
J. J	Water Well Contractor's Certification:
	This well was drilled under my jurisdiction and this report is
Vas a drive shoe used? Yes 🛘 No Plugs Size: location ft.	true to the best of my knowledge and belief.
old any strata contain unusable water? Yes No	Name Date (Person, firm or corporation) (Type or brint)
Type of water? 2alty depth of strata 475 45 509	Address 3032 Allen St. Keko, Wash, 98626
Nethod of sealing strata off Coment Grout 40 302 feet  Vas well gravel packed? ☐ Yes ☐ No Size of gravel:	[Signed] Dela McDha (Water Well Contractor)
Gravel placed fromft. toft.	Contractor's License No. 424 Date 4-4 1979
	19/ 19/