NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

WATER WELL REPORT GEIVED STATE OF OREGON JUL 251973tate Well No. 3.1

STATE ENGINEER, SALEM, OREGÓN 97310 within 30 days from the date of well completion.

(Please type or pring TATE ENGINEER No. (Do not write above this ling ALEM OREGON

(1) OWNER: 2	(10) LOCATION OF WELL:			
Name Warren Daso	County Clumber Driller's well number			
Address By 200A Sagagaaas Dro	14 14 Section 24 T. 3 N R. 2 W W.M.			
(9) MVDE OF WORK (-bb).	Bearing and distance from section or subdivision corner			
(2) TYPE OF WORK (check):	<u> </u>			
New Well	o •			
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.			
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 66 ft.			
Rotary Driven Domestic Industrial Municipal Domestic	Static level 30 ft. below land surface. Date 6-26-73			
Cable 17 Jetted	Artesian pressure lbs. per squar			· ·
CASING INSTALLED: Threaded Welded	(12) WELL LOG: Diameter of well below casing			
1 " Diam. from 6 ft. to 18 ft. Gage 250	Depth drilled ft. Depth of completed well ft.			
"Diam, from ft. to ft. Gage	Formation: Describe color, texture, grain size and structure of materials;			
PERFORATIONS: Perforated? \(\tau\) Yes \(\tau\) No.	and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.			
PERFORATIONS: Perforated? ☐ Yes ☑ No. Type of perforator used	MATERIAL	From	To 5	SWL
Size of perforations in. by in.	Top Soil	FX .	e/	
	the state	4		
perforations from ft. to ft ft ft.	Cher nellas	4 3	39	
perforations fromft. toft.			7	
	Sand light Brown	39	57	
(7) SCREENS: Well screen installed? Yes You		57		
Manufacturer's Name	Comput grand	75 /	<u>'S</u>	
Type Model No Diam Slot size Set from ft. to ft.			- d	
Diam. Slot size Set from ft. to ft. to ft.	large gravel	75 7	7 .9	
Digiti Slot Size	T 0761			-
(8) WELL TESTS: Drawdown is amount water level is lowered below static level				
Was a pump test made? ☐ Yes ☐ No If yes, by whom?				
Yield: gal./min. with ft. drawdown after hrs.				
" " "				
" " " "				
Bailer test S. gal./min. with () ft. drawdown after / hrs.		<u> </u>		
	i	-		
	Work started 6-25- 1973 Complete	7	727	73
rature of water Depth artesian flow encountered ft.		1 - 2	Aug.	19 /2
(9) CONSTRUCTION:	Date well drilling machine moved off of well	6 2		19 / 5
Well seal—Material used Completible	Drilling Machine Operator's Certification:		··	-•
Well sealed from land surface to 25 ft.	This well was constructed under my direct supervision. Materials used and information reported above are true to my			
Diameter of well bore to bottom of sealin.	best knowledge and belief,			
Diameter of well bore below seal	[Signed] Drilling Machine Operator)			
Number of sacks of cement used in well seal sacks	Drilling Machine Operator's License No.			
Number of sacks of bentonite used in well seal sacks Brand name of bentonite Allert B				
Number of pounds of bentonite per 100 gallons	Water Well Contractor's Certification:			
of waterlbs./100 gals.	This well was drilled under my jurisdiction and this report is			
Was a drive shoe used? ☐ Yes ☐ No Plugs Size: location ft.	true to the best of my knowledge and belief.			
Did any strata contain unusable water? Yes No	Name (Person, firm or corporation) (Type or print)			
Type of water? depth of strata	Address 840 We STST, ST. Hele us One			
Method of sealing strata off	Isimos Flankatilo	·		
Was well gravel packed? ☐ Yes ☑ No Size of gravel:	[Signed] (Water Well Contractor)			
Gravel placed from ft. to ft.	Contractor's License No. 420 Date 6-29, 19/0			
	<u> </u>			 ,