

NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

RECEIVED
NOV 6 1969

WATER WELL REPORT

STATE OF OREGON

STATE ENGINEER, SALEM, OREGON

within 30 days from the date of well completion.

STATE ENGINEER
SALEM, OREGON

(Please type or print)
(Do not write above this line)

State Well No. 4N/2W-16

State Permit No. 3522

(1) OWNER:

Name C. J. STEYACHT
Address RT 2, Box 185 Sherwood, Ore

(2) TYPE OF WORK (check):

New Well ☒ Deepening ☐ Reconditioning ☐ Abandon ☐

If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary ☒ Driven ☐
Cable ☐ Jetted ☐
Dug ☐ Bored ☐

(4) PROPOSED USE (check):

Domestic ☒ Industrial ☐ Municipal ☐
Irrigation ☐ Test Well ☐ Other ☐

(5) CASING INSTALLED:

Threaded ☐ Welded ☒
6" Diam. from 0 ft. to 100 ft. Gage 250
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

(6) PERFORATIONS:

Perforated? ☐ Yes ☒ No.

Type of perforator used

Size of perforations in. by in.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS:

Well screen installed? ☐ Yes ☒ No

Manufacturer's Name

Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WATER LEVEL: Completed well.

Static level 56 ft. below land surface Date 10-31-69

Artesian pressure lbs. per square inch Date

(9) WELL TESTS:

Drawdown is amount water level is lowered below static level

Was a pump test made? ☒ Yes ☐ No If yes, by whom? Operator

Well: 36 gal./min. with 64 ft. drawdown after 2 hrs.

" " " "

" " " "

Ball test gal./min. with ft. drawdown after hrs.

Artesian flow g.p.m. Date

Temperature of water 52° Was a chemical analysis made? ☐ Yes ☐ No

(10) CONSTRUCTION:

Well seal—Material used Bentonite & Clay

Depth of seal 0 to 80 ft.

Diameter of well bore to bottom of seal 9 in.

Were any loose strata cemented off? ☐ Yes ☒ No Depth

Was a drive shoe used? ☒ Yes ☐ No

Did any strata contain unusable water? ☐ Yes ☒ No

Type of water? depth of strata

Method of sealing strata off

Was well gravel packed? ☐ Yes ☒ No Size of gravel:

Gravel placed from ft. to ft.

(11) LOCATION OF WELL:

County Columbia Driller's well number 152
1/4 1/4 Section 16 T. 4N R. 2W W.M.

Bearing and distance from section or subdivision corner Tract

11

(12) WELL LOG:

Diameter of well below casing 6"

Depth drilled 120 ft. Depth of completed well 120 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level as drilling proceeds. Note drilling rates.

MATERIAL	From	To	SWL
Brown Soil	0	3	
Red Clay	3	42	
Brown Shale	42	104	
Brown, Red, yellow shale (water)	104	120	56

Work started 10-27 1969 Completed 10-31 1969

Date well drilling machine moved off of well 10-31 1969

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] Raymond P. Borders Date 10-31, 1969
(Drilling Machine Operator)

Drilling Machine Operator's License No. 305

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

NAME B. S. Drilling Co. (Person, firm or corporation) (Type or print)

Address RT 3, Box 271A Sherwood, Ore.

[Signed] Raymond P. Borders (Water Well Contractor)

Contractor's License No. 404 Date 10-31, 1969