STATE OF OREGON WATER SUPPLY WELL REPORT (as required by ORS 537.765 & OAR 690-205-0210)

1	2.	1	~	2	M	7
	/.=		n.	- /.	.,,	

WELL LABEL # L	90133
START CARD#	1002550

(1) LAND OWNER Owner Well I.D.			
	(9) LOCATION OF WELL (legal description)		
First Name QUINTIN Last Name PEASLEY	County Columbia Twp 4.00 N N/S Range 1.00 W E/W WM		
Company Address 10070 HWW 212	Sec <u>18</u> <u>SE</u> 1/4 of the <u>SE</u> 1/4 Tax Lot <u>1204</u>		
Address 19978 HWY. 213 City OREGON CITY State OR Zip 97045-7753	Tax Map Number Lot Lat " or DMS or DD		
	0 1 "		
(2) TYPE OF WORK New Well Deepening Conversion			
Alteration (repair/recondition) Abandonment	Street address of well Nearest address		
(2) DDILL METHOD	ACROSS FROM 34840 BENNETT RD. WARREN,OR 97053		
(3) DRILL METHOD Rotary Air Rotary Mud Cable Auger Cable Mud	WARREN, OR 97033		
Reverse Rotary Nutrul Cable Linger Cable Mudd	(10) STATIC WATER LEVEL Date SWL(psi) + SWL(ft)		
	Enjeting W-11 / Due to a ming		
(4) PROPOSED USE Domestic Irrigation Community	Existing Well / Predeepening 10-31-2007 32 35 32 35 35 36 36 36 36 3		
☐ Industrial/ Commericial ☐ Livestock ☐ Dewatering	Flowing Artesian? Dry Hole?		
Thermal Injection Other	WATER BEARING ZONES Depth water was first found 214		
(5) BORE HOLE CONSTRUCTION Special Standard Attach co			
Depth of Completed Well 319.00 ft.	yy) SWL Date From To Est Flow SWL(psi) + SWL(ft) 11-05-2007 214 215 10 65		
BORE HOLE SEAL sack			
Dia From To Material From To Amt lbs			
10 166 185.5 Cement 150 185.5 12 S			
8 185.5 387			
	(11) WELL LOG Ground Floration		
	Ground Elevation		
How was seal placed: Method A B C D E	Material From To Brown Weathered Basalt 166 170		
Other	100 170		
Backfill placed from ft. to ft. Material	C P 1		
Filter pack from ft. to ft. Material Size	Oray Basait 174 192		
Explosives used: Yes Type Amount	Brown Broken Weathered Basalt 214 215		
(6) CASING/LINER	Brown Weathered Basalt 215 245		
Casing Liner Dia + From To Gauge Stl Plstc Wld Thr			
●	Gray Broken Basalt 252 258		
\bigcirc	Gray Basalt 258 287		
	Gray Broken Basalt 287 288		
	Gray Basalt		
	Gray Broken Basalt 290 298		
Shoe Inside Outside Other Location of shoe(s) 185.5	Multicolored Broken Basalt 335 345		
Temp casing Yes Dia From To	Multicolored Weathered Basalt 345 387		
(7) PERFORATIONS/SCREENS			
Perforations Method Circular Saw			
Screens Type Material			
Perf/S Casing/ Screen Scrn/slot Slot # of Tele/ creen Liner Dia From To width length slots pipe siz	Date Started 10-31-2007 Completed 11-16-2007		
	(unbonded) Water Well Constructor Certification		
Perf Liner 299 318 .25 6 19 6	I certify that the work I performed on the construction, deepening, alteration, o		
	abandonment of this well is in compliance with Oregon water supply well		
	construction standards. Materials used and information reported above are true to		
	the best of my knowledge and belief.		
(8) WELL TESTS: Minimum testing time is 1 hour	License Number Date		
Pump Bailer	Electronically Filed		
Yield gal/min Drawdown Drill stem/Pump depth Duration (hr)	Signed		
93 385 1	(bonded) Water Well Constructor Certification		
	I accept responsibility for the construction, deepening, alteration, or abandonment		
	work performed on this well during the construction dates reported above. All work		
Temperature 59 °F Lab analysis Yes By	performed during this time is in compliance with Oregon water supply well		
Water quality concerns? Yes (describe below)	construction standards. This report is true to the best of my knowledge and belief.		
From To Description Amount Units	License Number <u>1679</u> Date <u>12-16-2007</u>		
33 80 Iron	Electronically Filed		
	Signed THOMAS R DANNISON JR (E-filed)		
	Contact Info (optional) <u>(503)543-8383</u>		