NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

## COOS STATE OF OREGON MAY 9 1973 state Well No. 21 1695 (Please type or pont) ATE ENGINE Termit No. ...... (Do not write above this line) EM OREGON

(1) OWNER:	(10) LOCATION OF WELL:
Name Lanny Mix	County (003 Driller's well number
Address 254 Shutters Landing Rd.	14 14 Section 2 T.248 R. 13 W.M.
North Bend, Oregon	Bearing and distance from section or subdivision corner
(2) TYPE OF WORK (check):	75
New Well ☐ Deepening ☐ Reconditioning ☐ Abandon ☐	
If abandonment, describe material and procedure in Item 12.	(11) MARNED TEXTEL. Completed well
	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 8 ft.
Rotary	Static level 25 ft. below land surface. Date 3/30/73
Dug ☐ Bored ☐ Irrigation ☐ Test Well ☐ Other ☐	- Artesian pressure lbs. per square inch. Date
(5) CASING INSTALLED: Threaded □ Welded 2	Depth drilled 1 blameter of well below casing 6  The Depth drilled 1 blameter of well below casing 6  The Depth of completed well 61 ft.  The Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.
Type of perforator used	MATERIAL From To SWL
Size of perforations in. by in.	Brn. clau 0 4
perforations from ft. to ft.	Fine Brn. sand 4 14
perforations fromft. toft.	Brn. clay 14 26
perforations from ft. to ft.	Brn. Et sand with clay 26 55
periorations from	Gray sand 55 61
(7) SCREENS: Well screen installed? ★ Yes □ No	
Manufacturer's Name Johnson	
Type Stainless Steel Model No.	
Diam. 5." Slot size	
Diam Slot size Set from ft. to ft.	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	
Was a pump test made? XYes   No If yes, by whom? Driller	
Yild: 12 gal./min. with 12 ft. drawdown after 1 hrs.	
" " "	
" " " "	
" " "	
Bailer test gal./min. with ft. drawdown after hrs.	
Artesian flow g.p.m.	
Depth artesian flow encountered ft.	Work started 3/26 1973 Completed 3/30 1573
(9) CONSTRUCTION:	Date well drilling machine moved off of well 3/30 1973
Well seal-Material used Bentonite, Gnout Cement	Drilling Machine Operator's Certification:
Well sealed from land surface toft.	This well was constructed under my direct supervision.  Materials used and information reported above are true to my
Diameter of well bore to bottom of seal	best knowledge and belief.
Diameter of well bore below see	[Signed] Thomas E. Banington Date 5-6, 1923
Number of sacks of cement used in well seal9sacks	(Drilling Machine Operator)
Number of sacks of bentonite used in well sealsacks	Drilling Machine Operator's License No. 356
Brand name of bentonite National	YYT-4 YYT-II Clauses stands Claudifications
Number of pounds of bentonite per 100 gallons	Water Well Contractor's Certification:
of waterlbs./100 gals.	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Was a drive shoe used? ☐ Yes 🗷 No Plugs Size: location ft.	0
Did any strata contain unusable water?   Yes  No	(Person, firm or corporation) (Type or print)
Type of water? depth of strata	Address North Bend, Oregon
Method of sealing strata off	A
Was well gravel packed? ☐ Yes X☐ No Size of gravel:	[Signed] (Water Well Contractor)
	Contractor's License No. 20/ Date 744 7 , 192
Gravel placed from ft. to ft.	Contractor & Literise No. S. L. Date