	4	· ·
NOTICE TO WATER WELL CONTRACTOR  The original and first copy of this report are to be filed with the	LL REPORT	
STATE ENGINEER SALEM OREGON 97310 \$ 27 1968	OREGON State Well No	24/13W-32
of well completion. ATE, ENGINEER	above this line) State Permit No.	ATTALLAND AND AND AND AND AND AND AND AND AND
(1) OWNER: Well # 46	(11) LOCATION OF WELL:	<u> </u>
Name Coos Bay - North Bend Water Board	County Coos Driller's well number	
Address P. O. Box 539, Coos Bay, Oregon		S R. 13W W.M.
	Bearing and distance from section or subdivision corner	
2) TYPE OF WORK (check):	Dours and distance from Section of Subdivision Country	
New Well		
3) TYPE OF WELL: (4) PROPOSED USE (check):	(10) TUTT I TOC	10.1
totary Driven Domestic Industrial Municipal X	(12) WELL LOG: Diameter of well be pepth drilled 190 ft. Depth of complete	
Oug 🔲 Bored 🖂   Irrigation 🖂 Test Well 🖂 Other 🖺	To post of complete	ica wen , ia
CASING INSTALLED: Threaded  Welded (5) Welded (5) Welded (5) Welded (5) Welded (5) Threaded (7) Welded (5) Threaded (7) Welded (5) Welded (5) Threaded (7) Welded (5)	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level as drilling proceeds. Note drilling rates.	
8" Diam from 190.0 ft to 180.0 ft Gage 277	MATERIAL	
8" Diam from 159.0 ft to 111.12 ft Gage .277		
8" TENERODA MICO 79.62 73.54 .277	Blow Sand Blow Sand, Light Blue & Gray	20 42
<del>K</del>	Light Gray Sand	
Type of perforator used	Very Light Gray & Coarse Sand	42 47 47 63
Size of perforations in. by in.	Coarse Light Brown Sand	63 80
perforations from ft. to ft.	Coarse Sand, Clay, & Shell	80 94
perforations fromft. toft.	Round Pea Size of Shell &	
perforations fromft. toft.	Sandstone	94 118
perforations fromft.	Sand Rock, Shell & Gravel	118 <del>1</del> 125
perforations from ft. to ft.		125   131
7) SCREENS: Well screen installed? XXYes  \[ \subseteq \text{No} \]		131 135
Manufacturer's Name Houston Well Screen	Very Coarse Sand w/ Small	
Type Stainless Steel Model No.		135 138
Diam. 8" Slot size 12 Set from 180,00 ft. to 159,00 ft.	Coarse Gray Sand Dark Gray Coarse Sand, Shell	145
Diam	1	145 160
(8) WATER LEVEL: Completed well. 79.62	Sand w/ Wood, Shell & a Little	
static level 5 ft. below land surface Date 4/1/68	l ' '	160 173
sesian pressure ————————————————————————————————————	1 TT	173 175
	Clay, Coarse Sand, Wood &	
(9) WELL TESTS: Drawdown is amount water level is lowered below static level	Clam Shells	175 180
Was a pump test made? 🔏 Yes 📋 No If yes, by whom?		180 190
gal./min. with 23 ft. drawdown after 31 hrs.	Work started 3/4/68 19 Completed	4/11/00
"	Date well drilling machine moved off of well	4/1/68 19
и и - и - и - и - и -	Drilling Machine Operator's Certification:	
Bailer test — gal./min. with — ft. drawdown after — hrs.	This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.	
Artesian flow g.p.m. Date		1/10/60 10
Temperature of water Was a chemical analysis made?  Yes XNo	[Signed] Drilling Machine Operator)	Date 4/12/68, 19
(10) CONSTRUCTION:  Vell seal—Material used Puddle Clay & Cement	Drilling Machine Operator's License No158	
Depth of seal18	Water Well Contractor's Certification:	
Diameter of well bore to bottom of sealin.	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.	
Were any loose strata cemented off?  Yes No Depth	NAME Casey Jones Well Drilling Co., Inc.	
Was a drive shoe used? Yes XXNo	(Person, firm or corporation) (Type or print)	
Old any strata contain unusable water? Yes No	Address Rt. 8, Box 695, Pleasant	Hill Oregon
Type of water? depth of strata	(1) 1/2 + 1/1	
Method of sealing strata off	[Signed] (Water Well Contractor)	
Vas well gravel packed? ☐ Yes 🔏 No Size of gravel:		•
Gravel placed fromft_ toft_	Contractor's License No. 103 Date	4/12/68, 19