The original and first copy

of this report are to be?

filed with the 1 1968

STATE ENGINEER, SALEM OREGON 97310

within 30 days from the date ... 4 1968

WATER WELL REPORT

STATE OF OREGON

(Please type or print) (Do not write above this line)

C00S	1	C64
2244 State Well No.	25/13W-	4 >

			05			,				-6.
2	2	4	Astate	Well	No.	25/1	3 w	, 	4	
_	2	-	,			7				

State Permit No.

of well completion ATE GILLINEER	G-4387
GALLIA OF GRON	(11) LOCATION OF WELL: #1
1) OWNER:	County Coos Driller's well number # 70
ame Douglas Veneer c/o Douglas Fir Plywood ddress P. O. Box 1088, Roasburg, Oregon	
ddress 1. 0. Dox 1000, noashalg, 016g0n	74 74 Bection 1. 10 W.M.
2) TYPE OF WORK (check):	Bearing and distance from section or subdivision corner
ew Well 🔊 Deepening 🗆 Reconditioning 🗍 Abandon 🖯	
abandonment, describe material and procedure in Item 12.	
3) TYPE OF WELL: (4) PROPOSED USE (check):	704
otary Driven D	(12) WELL LOG: Diameter of well below casing 10"
able	Depth drilled 120 ft. Depth of completed well 120 ft.
	Formation: Describe color, texture, grain size and structure of materials;
CASING INSTALLED: Threaded Welded X	and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change
10 " Diam. from 0 ft. to 77 ft. Gage • 307	in position of Static Water Level as drilling proceeds. Note drilling rates.
	MATERIAL From To SWL
" Diam. from	Brown Sand 0 35
PERFORATIONS: Perforated? Yes No.	Blow Gray Sand 35 100
ype of perforator used	Clam Shells Pebbles& Sand 100 120
ize of perforations in. by in.	
perforations from ft. to ft.	
perforations from ft. to ft.	
perforations from	
perforations fromft. toft.	
perforations fromft. toft.	
7) SCREENS: Well screen installed? ★ Yes □ No	
Manufacturer's Name Houston Well Screens	
ype Stainless Steel Model No.	
Diam. 8" Slot size #10 Set from 77 ft. to 120 ft.	
Diam Slot size Set from ft. to ft.	
8) WATER LEVEL: Completed well.	
tetic level 13 ft. below land surface Date 2/1/68	
lbs. per square inch Date	
9) WELL TESTS: Drawdown is amount water level is lowered below static level	
Vas a pump test made? ☐ Yes ▼ No If yes, by whom?	
gal./min. with ft. drawdown after hrs.	Work started 12/18/67 19 Completed 2/1/68 19
gar, mm. with the trawtown after ms.	Date well drilling machine moved off of well 2/1/68 19
	Drilling Machine Operator's Certification: This well was constructed under my direct supervision. Mate-
Bailer test 430 gal./min. with 21 ft. drawdown after 1 hrs.	rials used and information reported above are true to my best
Artesian flow g.p.m. Date	knowledge and belief.
Temperature of water Was a chemical analysis made? Yes XNo	[Signed] Date 2/9/68, 19
(10) CONSTRUCTION:	,
Well seal—Material used Puddle Clay & Cement	Drilling Machine Operator's License No. 158
Depth of seal 20 ft.	Water Well Contractor's Certification:
Diameter of well bore to bottom of sealin.	This well was drilled under my jurisdiction and this report is
Were any loose strata cemented off? Yes No Depth	true to the best of my knowledge and belief.
Was a drive shoe used? Yes A No	NAME Casey Jones Well Drilling Co. Inc. (Person, firm or corporation) (Type or print)
Did any strata contain unusable water? 🖸 Yes 🛂 No	
Type of water? depth of strata	Address Rt. 8, Box 695, Pleasant Hill, Oregon
Method of sealing strata off	to What of Janes
Vas well gravel packed? ☐ Yes 🕅 No Size of gravel:	[Signed] (Water Well Copyractor)
Fravel placed from the to the fit.	Contractor's License No. 103 Date 2/9/68 19
riavel maceu IIOIII TI TO	: VVIII G COLOR DE CO