NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

RECEIVED
OCT 29 1975
WATER RESOURCES DEPT.
SALEM, OREGON

WATER WELL REPORT
STATE OF OREGON
(Please type or print)
(Do not write above this line)

COOS 245

State Well No. 28s/12w-29
State Permit No.

(1) OWNER:
Name Arnold Acheson
Address Fairview Route, Box 1655
Coquille, Oregon

(2) TYPE OF WORK (check):
New Well ☒ Deepening ☐ Reconditioning ☐ Abandon ☐
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:
Rotary ☐ Driven ☐
Cable ☒ Jetted ☐
Dug ☐ Bored ☐

(4) PROPOSED USE (check):
Domestic ☒ Industrial ☐ Municipal ☐
Irrigation ☐ Test Well ☐ Other ☐

(5) CASING INSTALLED: Threaded ☐ Welded ☒
6" Diam. from 0 ft. to 68'-10" ft. Gage .280
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

(6) PERFORATIONS: Perforated? ☒ Yes ☐ No.
Type of perforator used Torch
Size of perforations 1/4 in. by 4 in.
4 perforations at 47 ft. to ft.
4 perforations from 52 ft. to ft.
4 perforations from 57 ft. to ft.
4 perforations from 62 ft. to ft.

(7) SCREENS: Well screen installed? ☐ Yes ☒ No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS: Drawdown is amount water level is lowered below static level
Was a pump test made? ☐ Yes ☒ No If yes, by whom?
Yield: gal./min. with ft. drawdown after hrs.
" " " "
" " " "
Bailer test 20 gal./min. with 5 ft. drawdown after 1 hrs.
Artesian flow g.p.m.
Temperature of water 52 Depth artesian flow encountered ft.

(9) CONSTRUCTION:
Well seal—Material used Bentonite & cement
Well sealed from land surface to 18 ft.
Diameter of well bore to bottom of seal 10 in.
Diameter of well bore below seal 6 in.
Number of sacks of cement used in well seal 1 sacks
Number of sacks of bentonite used in well seal 1 1/2 sacks
Brand name of bentonite Yellowstone
Number of pounds of bentonite per 100 gallons of water 100 lb./ 50 gal. lbs./100 gals.
Was a drive shoe used? ☒ Yes ☐ No Plugs Size: location ft.
Did any strata contain unusable water? ☐ Yes ☒ No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? ☐ Yes ☒ No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:
County Coos Driller's well number
NE ¼ SE ¼ Section 29 T. 28s R. 12w W.M.
Bearing and distance from section or subdivision corner
Lot 10 Plat of myrtle Heights

(11) WATER LEVEL: Completed well.
Depth at which water was first found 29 ft.
Static level 21 ft. below land surface. Date 10-14-75
Artesian pressure lbs. per square inch. Date

(12) WELL LOG: Diameter of well below casing 6
Depth drilled 70 ft. Depth of completed well 70 ft.
Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. *Report each change in position of Static Water Level and indicate principal water-bearing strata.*

MATERIAL	From	To	SWL
Claysoil brown	0	2	
Clay tan	2	10	
Clay brown	10	29	
Claystone fractured blue	29	70	

Work started Oct. 10 1975 Completed Oct. 14 1975
Date well drilling machine moved off of well Oct. 14 1975

Drilling Machine Operator's Certification:
This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] Andrew W. Miller (Drilling Machine Operator) Date 10-26, 1975
Drilling Machine Operator's License No. 469

Water Well Contractor's Certification:
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name George R. Miller & Son (Person, firm or corporation) (Type or print)
Address Route 1, Box 770 Bandon, Ore. 97411
[Signed] Andrew W. Miller (Water Well Contractor)
Contractor's License No. 600 Date Oct. 26, 1975

(USE ADDITIONAL SHEETS IF NECESSARY)

SP*45656-119