NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 973 within 30 days from the date of well completion.

STATE OF OREGON

(Please type or print) STATE ENGINEER

(Do not write above this line ALEM, OREGON State Permit No.

(1) OWNER:	(10) LOCATION OF WELL:
Name Henry Phillips	County COOS Driller's well number
Address Route 1, Box 46D Bandon Oregon	SE ¹ NW ₁₄ NE 1 ₄ section 29 T. 28s R. 14w W.M.
	Bearing and distance from section or subdivision corner
(2) TYPE OF WORK (check):	
New Well Deepening Reconditioning Abandon	
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 20 ft.
	Static level 8 ft. below land surface. Date 2-1-74
Rotary Driven Domestic Industrial Municipal Domestic Industrial Industrial Domestic Industrial In	
Dug Dolen Milgatton M. Lest Well Callet	Artesian pressure lbs. per square inch. Date
CASING INSTALLED: Threaded □ Welded K	(12) WELL LOG: Diameter of well below casing
6	Depth drilled 61½ ft. Depth of completed well 618311 ft.
" Diam, from ft. to ft. Gage	7, 7
"Diam. fromft. toft. Gage	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated,
	with at least one entry for each change of formation. Report each change in
PERFORATIONS: Perforated? ☐ Yes 🖽 No.	position of Static Water Level and indicate principal water-bearing strata.
Type of perforator used	MATERIAL From To SWL
Size of perforations in. by in.	
perforations from ft. to ft.	Sand hard packed tan 0 4
perforations fromft. toft.	Sand with clay tan 4 20 Sand with some gravel blue 20 61
perforations from ft. to ft.	Sand with some gravel blue 20 61
(E) (CONTEST	Claystone blue 61 61 61 61
(7) SCREENS: Well screen installed? Yes \(\text{No} \) No	
Manufacturer's Name Houston	
Type Stainless steel Model No. telescope	
Diam. 6 Slot size •008 Set from 521-6" ft. to 611-3" ft.	
Diam. Slot size Set from ft. to ft.	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	
I	
Was a pump test made? Tyes Ano If yes, by whom?	
Yield: gal./min. with ft. drawdown after hrs.	
n n	
Bailer test 40 gal./min. with 19 ft. drawdown after 1 hrs.	
	/· · · · · · · · · · · · · · · · · · ·
38	1 20 -71 0 4 71
perature of water 52 Depth artesian flow encountered ft.	Work started 1-30- 19 74 Completed 2-1- 19 74
(9) CONSTRUCTION:	Date well drilling machine moved off of well 2-1 1974
Well seal—Material used Bentonite	Drilling Machine Operator's Certification:
Well sealed from land surface to	This well was constructed under my direct supervision.
Diameter of well bore to bottom of sealin.	Materials used and information reported above are true to my best knowledge and belief,
Diameter of well bore below seal	
Number of sacks of cement used in well seal0	(Drilling Machine Operator)"
Number of sacks of bentonite used in well seal1sacks	Drilling Machine Operator's License No. 469
Brand name of bentonite Yellowstone	2.0
Number of pounds of bentonite per 100 gallons	Water Well Contractor's Certification:
of water 50 gal. / 100 lb. lbs./100 gals.	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Was a drive shoe used? ☐ Yes A No Plugs Size: location ft. Did any strata contain unusable water? ☐ Yes A No	Name George R. Miller & Son Well Drilling (Person, firm or corporation) (Type or print)
Type of water? depth of strata	Address Royle 1, Box 770 Bandon, Oregon
Method of sealing strata off	A man Pare Ol
Was well gravel packed? Yes No Size of gravel:	[Signed] (Water Well Contractor)
Gravel placed from ft. to ft.	Contractor's License No. 322 Date Febuary 8 , 1974
Att W assument Lt.	DOMESTICA D MACCADO ITO AND