

NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report
are to be filed with the

WATER RESOURCES DEPARTMENT
SALEM, OREGON 97310
within 30 days from the date
of well completion.

WATER WELL REPORT

RECEIVED

STATE OF OREGON
(Please type or print)

COOS

State Well No. 28s/14w-4ad

003745

State Permit No. G-7927

AUG 30 1977

(Do not write above this line)

(1) OWNER: WATER RESOURCES DEPT.

Name Rex Pierce SALEM, OREGON
Address Route 1, Box 1820
Coquille, Oregon 97423

(2) TYPE OF WORK (check):

New Well Deepening Reconditioning Abandon
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary Driven
Cable Jetted Domestic Industrial Municipal
Dug Bored Irrigation Test Well Other

(4) PROPOSED USE (check):

Domestic Industrial Municipal
Irrigation Test Well Other

(5) CASING INSTALLED:

Threaded Welded
8" Diam. from 0 ft. to 51'-5" ft. Gage 250
6" Diam. from 60'-9" ft. to 62'-9" ft. Gage 250
" Diam. from ft. to ft. Gage

(6) PERFORATIONS:

Perforated? Yes No.

Type of perforator used

Size of perforations in. by in.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS:

Well screen installed? Yes No

Manufacturer's Name Johnson
Type Stainless steel Model No. telescope
Diam. 8 Slot size .015 Set from 49'-8" ft. to 60'-9" ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level

Was a pump test made? Yes No If yes, by whom?
gal./min. with ft. drawdown after hrs.
" " " "
" " " "
Bailer test 40 gal./min. with 2 1/4 ft. drawdown after 1 hrs.
Artesian flow g.p.m.
Temperature of water 52 Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Well seal—Material used Bentonite & cement
Well sealed from land surface to 20 ft.
Diameter of well bore to bottom of seal 12 in.
Diameter of well bore below seal 8 in.
Number of sacks of cement used in well seal 2 sacks
How was cement grout placed? 3 sacks of bentonite
Grouted from surface

Was a drive shoe used? Yes No Plugs Size: location ft.
Did any strata contain unusable water? Yes No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? Yes No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County Coos Driller's well number
SE 1/4 NE 1/4 Section 4 T. 28S R. 14W W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found 11 ft.
Static level 11 ft. below land surface. Date 8-15-77
Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing 0

Depth drilled 69 ft. Depth of completed well 62'-9" ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
Bulldozed area			
Sand medium gray	0	14	
Sand coarse brown	14	18	
Sand muddy medium brown	18	26	
Sand muddy medium blue	26	35	
Sand muddy medium blue with Gravel and wood	35	48	
Sand medium blue	48	60	
Silty clay blue with shell	60	69	

Work started 8-9 1977 Completed 8-15 1977

Date well drilling machine moved off of well 8-15 1977

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] Andrew W. Miller Date 8-28, 1977
(Drilling Machine Operator)

Drilling Machine Operator's License No. 469

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

Name Bill Miller Well Drilling
(Person, firm or corporation) (Type or print)

Address Route 1, Box 1115 Bandon, Oregon 97411

[Signed] Andrew W. Miller
(Water Well Contractor)

Contractor's License No. 600 Date 8-28, 1977