

NOTICE TO WATER WELL CONTRACTOR
The original and first copy
of this report are to be
filed with the

COOS WATER WELL REPORT RECEIVED
STATE OF OREGON
JUN 15 1973
STATE ENGINEER
SALEM OREGON

28S/14W-29

STATE ENGINEER, SALEM, OREGON 97310
within 30 days from the date
of well completion.

(Do not write above this line)

State Well No. 28S/14W-29
State Permit No.

G-5263

(1) OWNER:

Name William Soper
Address P.O. Box 471 Bandon, Oregon

(2) TYPE OF WORK (check):

New Well Deepening Reconditioning Abandon

If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary Cable Dug
Driven Jetted Bored

(4) PROPOSED USE (check):

Domestic Industrial Municipal
Irrigation Test Well Other

CASING INSTALLED:

Threaded Welded
6" Diam. from 0 ft. to 54' 4" ft. Gage 250
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

PERFORATIONS:

Perforated? Yes No.

Type of perforator used

Size of perforations in. by in.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS:

Well screen installed? Yes No

Manufacturer's Name Johnson
Type Stainless steel Model No. telescope
Diam. 6 Slot size .008 Set from 53' 4" ft. to 58' 3" ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level

Was a pump test made? Yes No If yes, by whom?

Yield: gal./min. with ft. drawdown after hrs.
" " " " " "

Bailer test 30 gal./min. with 9 ft. drawdown after 1 hrs.

Artesian flow g.p.m.

Temperature of water 52 Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Well seal—Material used Bentonite
Well sealed from land surface to 18 ft.
Diameter of well bore to bottom of seal 9 in.
Diameter of well bore below seal 6 in.
Number of sacks of cement used in well seal 0 sacks
Number of sacks of bentonite used in well seal 2 sacks
Brand name of bentonite National baroid
Number of pounds of bentonite per 100 gallons of water XX lbs./100 gals.
Was a drive shoe used? Yes No Plugs Size: location ft.
Did any strata contain unusable water? Yes No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? Yes No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County Coos Driller's well number
NE 1/4 NE 1/4 Section 29 T. 28S R. 14W W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found 35 ft.
Static level 16 ft. below land surface. Date 6-13-73
Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing 0

Depth drilled 58 1/2 ft. Depth of completed well 58' 3" ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
Sandy soil red	0	4	
Sand fine tight tan	4	40	
Sand medium blue	40	53	
Sand coarse with 20% medium gravel blue	53	58 1/2	

Work started 6-11 1973 Completed 6-13 1973
Date well drilling machine moved off of well 6-13- 1973

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] George R. Miller Date 6-14 1973
(Drilling Machine Operator)

Drilling Machine Operator's License No. 469

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

Name George R. Miller & Son Well Drilling
(Person, firm or corporation) (Type or print)

Address Route 1 Box 770 Bandon, Oregon

[Signed] George R. Miller
(Water Well Contractor)

Contractor's License No. 322 Date June 14 1973