NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

WATER WELL REPORT RECEIVED OF OREGON

State Well

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date

(Please type or print)

NTo	285	/14w -29	7
NO.			

003946 State Permit No. OCT 1 0 1975 not write above this line) of well completion. G-7263 WATER RESOURCES DEPT. (10) LOCATION OF WELL: (1) OWNER: SALEM, OREGON Name William Soper COOS Driller's well number County Address P.O. Box 471 VEE NE 14 NE 1/2 Section 29 T. 28s R. 14w Bandon, Oregon Bearing and distance from section or subdivision corner (2) TYPE OF WORK (check): New Well Deepening [Reconditioning Abandon 🖂 If abandonment, describe material and procedure in Item 12. (11) WATER LEVEL: Completed well. (3) TYPE OF WELL: (4) PROPOSED USE (check): Depth at which water was first found Rotary Driven 🗀 Static level $21\frac{1}{3}$ ft. below land surface. Date 9-29-75 Cable Jetted 🛚 Bored | Dug Irrigation Test Well Other Artesian pressure lbs. per square inch. Date CASING INSTALLED: Threaded | Welded (12) WELL LOG: Diameter of well below casing ... 6 "Diam. from 0 ft. to 59 ft. Gage 280 Depth drilled 67 ft. Depth of completed well 67 ______ft. Gage _____ Formation: Describe color, texture, grain size and structure of materials; " Diam. from ft. to and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in PERFORATIONS: position of Static Water Level and indicate principal water-bearing strata. Perforated? Yes K No. Type of perforator used Size of perforations in, by in, Sandy soil brown perforations from ______ft. to _____ft. 0 perforations from _____ft. to _____ft. Sand hard brown 3 15 perforations from _____ ft. to _____ ft. Sand hard tan Muddy sand fine dark brown (7) SCREENS: Well screen installed? A Yes No Sand fine tan 27 29 Manufacturer's Name Johnson Peat & clay dark brown 29 Type Stainless steel Model No. telescope Sand medium grav Diam. 6 Slot size ... 008 Set from .58! ft. to 67! ft. Sand medium tan Diam. Slot size Set from Sand medium brown 60 67 Claystone gray (8) WELL TESTS: Drawdown is amount water level is lowered below static level Was a pump test made? Yes No If yes, by whom? gal./min. with ft, drawdown after hrs. Bailer test 30 gal./min. with 20 ft. drawdown after 1 hrs. g.p.m. perature of water 52 Depth artesian flow encountered Work started Sept. 25 1975 Completed Sept 29 1975 Date well drilling machine moved off of well (9) CONSTRUCTION: Drilling Machine Operator's Certification: Well seal-Material used Bentonite & cement. This well was constructed under my direct supervision. Well sealed from land surface to _____18 Materials used and information reported above are true to my best knowledge and belief. Diameter of well bore to bottom of seal _______10_ in. [Signed] Date 19-7 , 19 75 Diameter of well bore below seal ______6__ Number of sacks of cement used in well seal Drilling Machine Operator's License No. Number of sacks of bentonite used in well seal _____2 Brand name of bentonite Yellogstone Water Well Contractor's Certification: Number of pounds of bentonite per 100 gallons This well was drilled under my jurisdiction and this report is of water 100 lb./50 gal. lbs./100 gals. true to the best of my knowledge and belief. Was a drive shoe used? Yes No Plugs Size: location ft. Name George R. Miller & Son Did any strata contain unusable water?

Yes
No (Person, firm or corporation) (Type or print) Address Route 1 .. Box 770 Bandon . Oregon 97411 Type of water? [Signed] (Water Well Contractor) Method of sealing strata off Was well gravel packed? Yes No Size of gravel:

ft. to _____ ft.

Contractor's License No. 600 Date Oct. 7