

NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

WATER WELL REPORT

WATER RESOURCES DEPARTMENT SALEM, OREGON 97300 within 30 days from the date of well completion.

RECEIVED

STATE OF OREGON (Please type or print)

COOS

State Well No. 295/14096d

State Permit No.

SEP 22 1977

(Do not write above this line)

004252

(1) OWNER: WATER RESOURCES DEPT. Name Fred Cox SALEM, OREGON Address P.O. Box 932 Bandon, Oregon

(2) TYPE OF WORK (check): New Well [X] Deepening [] Reconditioning [] Abandon [] If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL: Rotary [] Cable [X] Dug [] Driven [] Jetted [] Bored [] (4) PROPOSED USE (check): Domestic [] Industrial [] Municipal [] Irrigation [X] Test Well [] Other []

CASING INSTALLED: Threaded [] Welded [X] 4 1/2" Diam. from 0 ft. to 41'-6" ft. Gage 2.50

PERFORATIONS: Perforated? [] Yes [X] No. Size of perforations in. by in. perforations from ft. to ft.

(7) SCREENS: Well screen installed? [X] Yes [] No Manufacturer's Name Johnson Type Stainless steel Model No. telescope Diam. 8 Slot size .040 Set from 40'-3" ft. to 46'-3" ft.

(8) WELL TESTS: Drawdown is amount water level is lowered below static level Was a pump test made? [] Yes [X] No Yield: gal./min. with ft. drawdown after hrs. Bailer test 30 gal./min. with 9 ft. drawdown after 1 hrs. Artesian flow g.p.m. Temperature of water 52 Depth artesian flow encountered ft.

(9) CONSTRUCTION: Well seal—Material used Cement Well sealed from land surface to 18 ft. Diameter of well bore to bottom of seal 12 in. Diameter of well bore below seal 8 in. Number of sacks of cement used in well seal 9 sacks How was cement grout placed? grouted from surface Was a drive shoe used? [] Yes [X] No Plugs Size: location ft. Did any strata contain unusable water? [] Yes [X] No Type of water? depth of strata Method of sealing strata off Was well gravel packed? [] Yes [X] No Size of gravel: Gravel placed from ft. to ft.

(10) LOCATION OF WELL: County Coos Driller's well number SE 1/4 NW 1/4 Section 8 T. 29S R. 14W W.M. Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well. Depth at which water was first found 17 ft. Static level 9 ft. below land surface. Date 9-12-77 Artesian pressure lbs. per square inch. Date

(12) WELL LOG: Diameter of well below casing 0 Depth drilled 46 ft. Depth of completed well 46 ft. Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

Table with columns: MATERIAL, From, To, SWL. Rows include: Sandy soil gray (0-1), Sand with clay brown (1-17), Sand fine tan (17-29), Sand medium tan (29-36), Sand coarse tan (36-38), Fine gravel and coarse sand (38-46), Claystone blue (46-).

Work started 8-17 1977 Completed 9-12 1977 Date well drilling machine moved off of well 9-12 1977

Drilling Machine Operator's Certification: This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief. [Signed] (Bill Miller) Date 9-18, 1977. Drilling Machine Operator's License No. 469

Water Well Contractor's Certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Name Bill Miller Well Drilling (Person, firm or corporation) (Type or print) Address Route 1, Box 1115 Bandon, Oregon [Signed] (Bill Miller) (Water Well Contractor) Contractor's License No. 600 Date 9-18, 1977