FEB 1 8 1998

RECEIVED

WELL I.D.# 4/8220

9.1	WII	S OI	OKE	OON	
WAT	ER	SUP	PLY	WELL	REPORT

WATER SUPPLY WELL REPORT
(as required by ORS 537.765)

Instructions for completing this report are on the last page of this form. SALEM, OREGON

[Instruction of the completing this report are on the last page of this form. SALEM, OREGON]

(1) OWNER: Well Number 9802		WELL by legal des			
Name Dave Hughs	County Coo.			gitude	<del></del>
Address 1485 Croft Rd		N or Range		_ E o(V	v. w.m.
City Baudon State OR Zip9741				1/4 bdivision	
(2) TYPE OF WORK	Tax Lot <u>700</u>	ell (or nearest address)			Dr P
New Well Deepening Alteration (repair/recondition) Abandonment  (3) DRILL METHOD:	<u> </u>	T.	BONDO	NOF	2
Rotary Air Rotary Mud Cable Auger	(10) STATIC WATE		_		1 7 0
Other	=	clow land surface.		)ate <u>/-2</u>	
(4) PROPOSED USE:	Artesian pressure		are inch. D	ate	
Domestic Community Industrial Irrigation	(11) WATER BEAR	ang zones:			
Thermal Injection Livestock Other	=		n'		
(5) BORE HOLE CONSTRUCTION:	Depth at which water w	as first found	<u> </u>		
Special Construction approval Yes No Depth of Completed Well		Т-	Estimated	Flow Rate	SWL
Explosives used Yes No Type Amount	From 32	70 48			9
HOLE SEAL	1 32	+ 70	999	077	
Diameter From To Material From To Sacksor pounds		<del>-  </del>	1		
12' 0 20 BONT 20 0 25	-		<del> </del>		
5// 4 5 //0	- [		<del> </del>		
8" 2048			<del></del>		
	(12) WELL LOG:	40	m'		
How was seal placed: Method A B C D E	Groun	nd Elevation +-52			
& Other Poured from Surface	Mater		From	То	SWL
Backfill placed from ft. to ft. Material		y CIMY	rioin (2)	10	SWL
Gravel placed from ft. to ft. Size of gravel	=			6	
(6) CASING/LINER:		and	- 8	26	9
Diameter From To Gauge Steel Plastic Welded Threader		ord STONG	_ 0	37	
Casing: 8 + 7 48 250 0 0	Brow So	NE > TONE	26	3.0	
	Sand		1 32	110	-
	1 1 -	ogrs e sa	ve 30	70	
	Jacque C		48		
Liner: 6' -3 28 sch 40 R B	Blue	=1024	70		
		-	-		
Final location of shoe(s)	<b>-</b>   <del> </del>				$\vdash$
(7) PERFORATIONS/SCREENS:			<del></del>		<b></b>
Perforations Method Torch	-				<b>-</b>
Screens Type Wesco Material PVC					<b></b>
From To size Number Diameter size Casing Line	r				ļ
30 48 44 36 8 B				-	<u> </u>
				-	<del> </del>
					<del></del>
28 48 020 6"					<del></del>
					<del></del>
	-	n 60		<u> </u>	00
(8) WELL TESTS: Minimum testing time is 1 hour	Date started		npleted	-67-	78
Flowing	(unbonded) Water We				
Pump Bailer Air Artesian	I certify that the wor of this well is in compli	k I performed on the co			
Yield gal/min Drawdown Drill stem at Time	<ul> <li>Materials used and info</li> </ul>				
999pm 48 (1h).	and belief.	_			
	-		WWC Nun		
	Signed			Date	
Temperature of water 52° Depth Artesian Flow Found	(bonded) Water Well (				
Was a water analysis done? Yes By whom	I accept responsibility	y for the construction, a	lteration, or aba	ndonment v	work
Did any strata contain water not suitable for intended use?	performed on this well of performed during this ti				
Salty Muddy Odor Colored Other	construction standards.	This report is true to the	e best of my kno	owledge and	belief.
Depth of strata:			, WWC Nur	nber <u>//</u>	209
•	Signed Hary	us Seen	le	Date 2	7.9
ORIGINAL & FIRST COPY-WATER RESOURCES DEPARTMENT S	SECOND COPY COMST	RUCTOR THIRE	COPY-CUST	OMER	