## STATE OF OREGON WATER SUPPLY WELL REPORT (as required by ORS 537.765 & OAR 690-205-0210)

WELL LABEL # L	81718
STADT CADD#	1000477

(1) LAND OWNER Owner Well I.D. 1183 W-6	(a) I OCATION OF WELL (1 11 1 2 2 )		
	(9) LOCATION OF WELL (legal description)		
First Name Dennis Last Name Olson	County Coos Twp 27.00 S N/S Range 14.0		
Company BALLY BANDON SHEEP RANCH	Sec <u>20</u> <u>SW</u> <u>1/4 of the <u>SW</u> <u>1/4</u> Tax Lot</u>	400	
Address PO BOX 1756	Tax Map Number Lot		
City BANDON State OR Zip 97411	Lat ' ' or	DMS or DD	
(2) TYPE OF WORK New Well Deepening Conversion	Long or	DMS or DD	
Alteration (repair/recondition) Abandonment	<ul> <li>Street address of well</li> <li>Nearest address</li> </ul>		
	88500 Whisky Run Road, Bandon		
(3) DRILL METHOD	66500 Willsky Rull Road, Balldoll		
Rotary Air Rotary Mud Cable Auger Cable Mud	(10) STATIC WATER LEVEL		
Reverse Rotary Other	Date SWL(ps1)	+ SWL(ft)	
(4) PROPOSED USE Domestic Irrigation Community	Existing Well / Predeepening		
	Completed Well 03-29-2007	34	
	Flowing Artesian? Dry Hole?		
Thermal Injection Other	WATER BEARING ZONES Depth water was first fou	nd 34	
(5) BORE HOLE CONSTRUCTION Special Standard Attach copy)		i) + SWL(ft)	
Depth of Completed Well 65.00 ft.	03-29-2007 34 62 100	34	
BORE HOLE SEAL sacks/		_	
Dia From To Material From To Amt lbs		<b></b>	
16 0 4 Bentonite 0 4 3 S		<b></b>	
12.25 4 65 Bentonite 4 32 22 S			
0 03 70	(11) WELL LOG Ground Elevation 200		
How was seal placed: Method A B C D E	<del></del>		
	Material From Topsoil 0	To 2	
Other Pour from surface	Cemented sand brown 2	3	
Backfill placed from ft. to ft. Material Filter pack from 32 ft. to 70 ft. Material Sand Size 8/12	Wood & peat 3	4	
	Cemented sand brown 4	5	
Explosives used: Yes Type Amount	Sand fine-medium tan 5	16	
(6) CASING/LINER	Sandy clay tan & orange 16	18	
Casing Liner Dia + From To Gauge Stl Plstc Wld Thrd	Sand fine-coarse brown 18	31	
● 10 × 1.5 4 .250 ● □ □	Sandy clay tan w/sand fine-coarse brown 31	32	
8   1.08   52.5   sdr26	Sand fine-coarse brown 32 Sand fine-coarse w/gravel fine brown 44	50	
● 8	Sandy clay tan w/gravel fine & sand f-c brown 50	52	
	Gravel fine w/sand coarse-fine brown 52	55	
	Gravel fine w/sand c-f & sandy clay orange brown 55	57	
Shoe Inside Outside Other Location of shoe(s)	Gravel fine-medium w/sand coarse-fine gray brown 57	60	
Temp casing Yes Dia From To	Gravel fine-medium w/sand c-f & sandy clay tan 60	61	
(7) PERFORATIONS/SCREENS	Gravel fine-medium w/sand coarse-fine gray brown 61	62	
Perforations Method	Claystone gray 62	70	
Screens Type Johnson V-Wire Material Stainless Steel			
**			
Perf/ Casing/ Screen Screen Liner Dia From To width length slots pipe size	Date Started 01-11-2007 Completed 03-29-20	07	
Screen         8         52.5         62.5         .061         8	(unbonded) Water Well Constructor Certification		
0 0210 001	I certify that the work I performed on the construction, deep	pening alteration or	
	abandonment of this well is in compliance with Oregon	<i>U</i> ,	
	construction standards. Materials used and information repor		
	the best of my knowledge and belief.		
(8) WELL TESTS: Minimum testing time is 1 hour	License Number Date		
Pump	Electronically Filed		
Yield gal/min Drawdown Drill stem/Pump depth Duration (hr)	Signed		
83.8 11.5 63 1	(bonded) Water Well Constructor Certification	<u> </u>	
02.5 11.0 (2) (bolided) Water Well Collistration			
	I accept responsibility for the construction, deepening, alteration, or abandonmen work performed on this well during the construction dates reported above. All work		
Temperature 53 °F Lab analysis Yes By	performed during this time is in compliance with Oregon water supply well		
Water quality concerns? Yes (describe below)	construction standards. This report is true to the best of my knowledge and belief.		
From To Description Amount Units License Number 1493 Date03-30-2007			
· ·	Electronically Filed		
	Signed JAMES A MACK SR (E-filed)		
	Contact Info (optional) BANDON WELL & PUMP COMPAN	Y (541) 347-7867	
ODICINAL WATER RESOURCES F			