STATE OF OREGON WATER SUPPLY WELL REPORT (as required by ORS 537.765 & OAR 690-205-0210)

07-18-2008

WELL LABEL # L	91192
START CARD#	122872

(1) LAND OWNER Owner Well I.D. 1265 (Shuman)	(9) LOCATION OF WELL (legal description)	
First Name Michael Last Name Keiser	County Coos Twp 27.00 S N/S Range 14.00 W E/W WM	
Company Bandon Dunes	Sec 29 NW 1/4 of the SE 1/4 Tax Lot 1300	
Address 57744 Round Lake Drive	Tax Map Number Lot	
City Bandon State OR Zip 97411	Lat " or DMS or DD Long " or DMS or DD	
(2) TYPE OF WORK New Well Deepening Conversion	Long or DMS or DD	
Alteration (repair/recondition) Abandonment	Street address of well Nearest address F77.4 A Parad Lake Deires	
(3) DRILL METHOD	57744 Round Lake Drive	
Rotary Air Rotary Mud Cable Auger Cable Mud Reverse Rotary Other	(10) STATIC WATER LEVEL Date SWL(psi) + SWL(ft)	
(4) PROPOSED USE Domestic Irrigation Community	Existing Well / Predeepening	
Industrial/ Commercial Livestock Dewatering	Completed Well 07-09-2008 33.6	
Thermal Injection Other	Flowing Artesian? Dry Hole?	
	WATER BEARING ZONES Depth water was first found 33.58	
(5) BORE HOLE CONSTRUCTION Special Standard Attach copy Depth of Completed Well 70.33 ft.		
BORE HOLE SEAL sacks	07-03-2008 33.58 66 125 33.6	
Dia From To Material From To Amt lbs		
15 0 71 Bentonite 0 30 30 S		
6 71 78 Cement 72 78 1 S		
	(11) WELL LOG Ground Elevation 100	
How was seal placed: Method A B C D E	Material From To	
Other Pour from surface	Sandy clay brown 0 2	
Backfill placed from ft. to ft. Material	Cemented sand brown 2 3	
Filter pack from 30 ft. to 71 ft. Material Sand Size 6/9 8/12	Sand fine tan brown 3 23 Sandy clay white 23 24	
Explosives used: Yes Type Amount	C-1 f t-1	
(6) CASING/LINER	Sand time tan Sand c-f w/gravel fine orange & sandy clay tan 37 39	
Casing Liner Dia + From To Gauge Stl Plstc Wld Thrd	Sand coarse-fine brown 39 52	
	Sand coarse-fine w/gravel fine brown 52 60	
0 10 10 51.33 sch40 0 0 X 1 66.33 70.33 sch40 0 0 X	Gravel fine-medium w/sand coarse-fine gray brown 60 65	
● ☐ 13.5 ☐ 1.5 ☐ 4 ☐ .250 ☐ ☐ ☐	Gravel medium-fine w/ sand c-f gray & wood 65 66 Clay gray 66 68	
	Clay gray 66 68 Claystone gray 68 75	
	Sandstone gray 75 78	
Shoe Inside Outside Other Location of shoe(s)		
Temp casing Yes Dia From To		
(7) PERFORATIONS/SCREENS		
Perforations Method		
Screens Type Johnson V-Wire Material S S		
Perf/S Casing/ Screen Scrn/slot Slot # of Tele/ creen Liner Dia From To width length slots pipe size	Date Started 05-01-2008 Completed 07-09-2008	
Screen 10 51.33 60.33 .031 10	(unbonded) Water Well Constructor Certification	
Screen 10 60.33 66.33 .075 10	I certify that the work I performed on the construction, deepening, alteration, or abandonment of this well is in compliance with Oregon water supply well	
	construction standards. Materials used and information reported above are true to	
	the best of my knowledge and belief.	
(8) WELL TESTS: Minimum testing time is 1 hour	License Number1759	
Pump	Electronically Filed	
Yield gal/min Drawdown Drill stem/Pump depth Duration (hr)	Signed <u>CHRISTOPHER L KERSEY (E-filed)</u>	
122 16.2 66 72	(bonded) Water Well Constructor Certification	
	I accept responsibility for the construction, deepening, alteration, or abandonment	
Temperature 54 °F Lab analysis Yes By	work performed on this well during the construction dates reported above. All work performed during this time is in compliance with Oregon water supply well	
Temperature 54 °F Lab analysis Yes By Water quality concerns? Yes (describe below)	construction standards. This report is true to the best of my knowledge and belief.	
From To Description Amount Units	License Number 1493 Date 07-18-2008	
•	Electronically Filed	
	Signed JAMES A MACK SR (E-filed)	
	Contact Info (optional) BANDON WELL & PUMP COMPANY (541) 347-7867	