NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the WATER WEI WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310 within 30 days from the date of well completion. (Do not write all	or print) State Permit No
(1) OWNER: Name: Baptist Church Address Frinewille Or. 97754	(10) LOCATION OF WELL: County CROOK Driller's well number 2 SW 4 NW 4 Section 36 T. 145 R. 15E W.M.
(2) TYPE OF WORK (check): New Well Deepening Reconditioning Abandon I If abandonment, describe material and procedure in Item 12.	Dearing and distance from section or subdivision corner Off Madeas sighway (11) WATER LEVEL: Completed well.

Address Hinewille Or. 99754	5W 14 NW 14 Section 36 T. 145 R. /	SE W.M.
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivision corner	
	Off MADRAS Highway	
New Well Deepening Reconditioning Abandon I If abandonment, describe material and procedure in Item 12.		
(3) TYPE OF WELL: (4) PROPOSED USE (check):	(11) WATER LEVEL: Completed well.	
Potons II Deliver II	Depth at which water was first found 25 ft.	
Jetted Domestic Industrial Municipal	Static level 60 ft. below land surface.	Date 15 Oct
Bored Irrigation Test Well Other	Artesian pressure lbs. per square inch.	Date
(5) CASING INSTALLED: Threaded Welded D	(12) WELL LOG: Diameter of well below of	. 10"
OOft. to _220ft. Gage . 250_	Denth drilled 230 st Porth of completed 230	
"Diam. fromft. toft. Gage	Formation: Describe color, texture, grain size and stru	
	and show thickness and nature of each stratum and	aguifer penetrated
(6) PERFORATIONS: Perforated? ☐ Yes ☑ No.	with at least one entry for each change of formation. Reposition of Static Water Level and indicate principal w	port each change in ater-bearing strata.
Type of perforator used	MATERIAL From	To SWL
Size of perforations in, by in.	Top Soil 0	3
perforations fromft. toft.	BROWN SAND + GRAVEL 3	26 60
perforations from ft. to ft.	Blue GRAY Clay 26	229
perforations from ft. toft.	PEA GRAVEL 229	230
	Water GEARING	-
(7) SCREENS: Well screen installed? Yes No		
Manufacturer's Name		
Type Model No.		
Diam. Slot size Set from ft. to ft.	<u> </u>	
Diam. Slot sizeSet fromft. toft.	4	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	RECEIVED	
a pump test made? Yes No If yes, by whom?	OCT 131979	
Yield: gal./min. with ft. drawdown after hrs.	WATER RESOURCES DEPT	
H H H	SALEM, OREGON	
" " "		
Beller test 50 gal./min. with Oft. drawdown after / hrs.		
estan flow g.p.m.	and the same of th	
Temperature of water 55 Depth artesian flow encounteredft.	Work started 3 Oct 1979 Completed /2	Oct 1979
(9) CONSTRUCTION:	Date well drilling machine moved off of well 15	Oct 1979
Well seal-Material used CEMENT	Drilling Machine Operator's Certification:	
Well sealed from land surface toft.	This well was constructed under my direct	t supervision.
Diameter of well bore to bottom of sealin_	Materials used and information reported above are true to my best knowledge and belief.	
Diameter of well bore below seal in.	[Signed] Lobby & Barnes Date / 50ct 1979	
Number of sacks of cement used in well sealsacks	(Drilling Machine Operator)	
How was cement grout placed?	Drilling Machine Operator's License No	
	Water Well Contractor's Certification:	سادية وينسده بوسور
	This well was drilled under my jurisdiction as	nd this report is
Was a drive shoe used? Yes No Plugs Size: location ft.	true to the best of my knowledge and belief.	
Did any strata contain unusable water? Yes No	Name Coss (Corporation) (Type or pute)	
Type of water? depth of strata	Address POBOX 35/ PM	ype or print)
Method of sealing strata off	RII PR	interbrante de fake dom
Was well gravel packed? ☐ Yes No Size of gravel:	[Signed]	
Gravel placed fromft. toft.	643 1001	SA
It.	Contractor's License No.	