

NOTICE TO WATER WELL CONTRACTOR  
The original and first copy of this report  
are to be filed with

CROO 1279

RECEIVED

WATER WELL REPORT

WATER RESOURCES DEPARTMENT,  
SALEM, OREGON 97310  
within 30 days from the date  
of well completion.

STATE OF OREGON  
(Please type or print)

State Well No. 145/16E-26ca

State Permit No. ....

WATER RESOURCES DEPT.

CROO  
1279

(1) OWNER: SALEM, OREGON  
Name W. E. Haynes  
Address P.O. Box 160 Prineville Ore 97254

(2) TYPE OF WORK (check):  
New Well  Deepening  Reconditioning  Abandon   
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL: (4) PROPOSED USE (check):  
Rotary  Driven  Domestic  Industrial  Municipal   
Cable  Jetted  Irrigation  Test Well  Other   
Dug  Bored

CASING INSTALLED: Threaded  Welded   
12" Diam. from 7.2 ft. to 48 ft. Gage 250  
8" Diam. from 7.2 ft. to 110 ft. Gage 188  
liner pipe

PERFORATIONS: Perforated?  Yes  No.  
Type of perforator used metal saw  
Size of perforations 1/8 in. by 3 in.  
1200 perforations from 50 ft. to 110 ft.

(7) SCREENS: Well screen installed?  Yes  No  
Manufacturer's Name .....  
Type ..... Model No. ....  
Diam. .... Slot size ..... Set from ..... ft. to ..... ft.  
Diam. .... Slot size ..... Set from ..... ft. to ..... ft.

(8) WELL TESTS: Drawdown is amount water level is lowered below static level  
Was a pump test made?  Yes  No If yes, by whom?  
Yield: gal./min. with ft. drawdown after hrs.  
" " " " "  
" " " " "  
Bailer test 50 gal./min. with 4 ft. drawdown after 1 hrs.  
Artesian flow none g.p.m.  
Temperature of water 56° Depth artesian flow encountered none ft.

(9) CONSTRUCTION: Well seal—Material used Cement  
Well sealed from land surface to 25 ft.  
Diameter of well bore to bottom of seal 16 in.  
Diameter of well bore below seal 12 in.  
Number of sacks of cement used in well seal 25 sacks  
How was cement grout placed? with grout pump and 25 ft. of pipe placed outside of the casing  
Was a drive shoe used?  Yes  No Plugs ..... Size: location ..... ft.  
Did any strata contain unusable water?  Yes  No  
Type of water? depth of strata  
Method of sealing strata off  
Was well gravel packed?  Yes  No Size of gravel: 1/4 minus  
Gravel placed from 25 ft. to 120 ft.

(10) LOCATION OF WELL:  
County Crook Driller's well number 554  
NE 1/4 SW 1/4 Section 26 T. 14S R. 16E W.M.  
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.  
Depth at which water was first found 50 ft.  
Static level 45 ft. below land surface. Date 12-9-78  
Artesian pressure none lbs. per square inch. Date

(12) WELL LOG: Diameter of well below casing 8"  
Depth drilled 112 ft. Depth of completed well 112 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
Sand; clay	0	15	
TAN clay	15	50	
Sand (water bearing)	50	65	45
Sand; green gravel (water bearing)	65	87	45
Sand; (water bearing)	87	108	45
sand; clay	108	110	45

Work started 12/4 1978 Completed 12-9 1978  
Date well drilling machine moved off of well 12-9 1978

Drilling Machine Operator's Certification:  
This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.  
[Signed] Archie Fox Date 1-10, 1979  
(Drilling Machine Operator)  
Drilling Machine Operator's License No. 389

Water Well Contractor's Certification:  
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.  
Name Archie Fox, Well Drilling  
(Person, firm or corporation) (Type or print)  
Address Rt. 3 Box 202 Prineville, Ore 97254  
[Signed] Archie Fox  
(Water Well Contractor)  
Contractor's License No. 444 Date 1-10, 1979