NOTICE TO WATER WELL CONTRACTOR . The original and first copy of this report are to be filed with the

WATER RESOURCES DEPARTMENT. SALEM, OREGON 97310 within 30 days from the date of well completion.

CROO 1339 WATER WELL REPORT

STATE OF OREGON

(Please type or print)

(Do not write above this line)

(1) OWNER: 46 ShowN CROSROADS	(10) LOCATION OF WELL:
Name PAUL HURAIS SUBDIVISION	County CROOK Driller's well number 41-C
Address 53,5 W. 5±4	5, E 4 N. W 4 Section 29 T. 145 R. 16 E W.M.
X city? PRINTUINC, CRE. 91754	Bearing and distance from section or subdivision corner
(2) TYPE OF WORK (check):	
New Well Deepening Reconditioning Abandon	
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found ft.
Rotary Driven Domestic Industrial Municipal	Static level // ft. below land surface. Date /0//5-/7
Dug	Artesian pressure
CASING INSTALLED: Threaded Welded	(40)
mreaded welded welded welded to the state of	(12) WELL LOG: Diameter of well below casing
"Diam from ft. to ft. Gage	Depth drilled 5B ft. Depth of completed well 5B ft.
" Diam. from ft. to ft. Gage	Formation: Describe color, texture, grain size and structure of materials;
	and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in
) PERFORATIONS: Perforated? Yes No.	position of Static Water Level and indicate principal water-bearing strata.
Type of perforator used Thorom	MATERIAL From To SWL
Size of perforations 1/16 in. by 8 in.	TOP Soil 0 4
	BROWN CIAY 4 8
perforations from ft. to ft.	CLAY & GRAVEL 8 9
perforations from ft. to ft.	Mad Cill End Wa 25 FD 121
(7) SCREENS: Well screen installed? Yes No	MEG. PINE SHALL YOU AS DE TAY
Manufacturer's Name	
Type Model No	
Diam, Slot size Set from ft. to ft.	
Diam, Slot size Set from ft. to ft.	PECFILE.
(8) WELL TESTS: Drawdown is amount water level is	- BEDZINED FOR
lowered below static level	NUV - 5 1979 SALEM DESCRICES DESCRIPTION
Was a pump test made? Yes No If yes, by whom?	NUV - 5 1979 SALES URCES DE
d: gal./min. with ft. drawdown after hrs.	WATER RESOURCES DEPT
" " " "	WATER RESOURCES DEPT
" " " "	SALEM, OREGON
Bailer test 40 gal./min. with omft. drawdown after 2 hrs.	
A sian flow NONE g.p.m.	
perature of water 56 Depth artesian flow encountered ft.	Work started 10/15 1979 Completed 10/16 1979
(9) CONSTRUCTION:	Date well drilling machine moved off of well 1979
Well seal—Material used CEMENT BROUT	Drilling Machine Operator's Certification:
Well sealed from land surface toft.	This well was constructed under my direct supervision. Materials used and information reported above are true to my
Diameter of well bore to bottom of seal [3" in.	best knowledge and beliefo
Diameter of well bore below sealin.	[Signed]
Number of sacks of cement used in well seal sacks	Drilling Machine Operator's License No. 1237
How was cement grout placed? PUMPED WITH GROUT PUMP, PIACED FROM	
BOTTOM-UP.	Water Well Contractor's Certification:
.,	This well was drilled under my jurisdiction and this report is
Was a drive shoe used? Yes No Plugs Size: location ft.	true to the best of my knowledge and belief.
Did any strata contain unusable water? X Yes No	(Person, firm or corporation) (Type or print)
Type of water? Shallow depth of strata 8	Address RT. 1, BOX 780 PRINOUILE, ORE.
Method of sealing strata off CEMENT GROUT	[Signed] Cut Clauson
Was well gravel packed? Yes \(\) No Size of gravel: /4Minus.	(Water Well Contractor)
Gravel placed from 25 ft. to 58 ft.	Contractor's License No. 74/ Date 10/18 , 1979