NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the
STATE ENGINEER, SALEM, OREGON 97310
within 30 days from the date of well completion.

CROO 1403

WATER WELL REPORT
STATE OF OREGON
(Please type or print)
(Do not write above this line)

RECEIVED JUN 2 1976 WATER RESOURCES DEPT. SALEM, OREGON

State Well No. .....
State Permit No. 14S/16E-30

(1) OWNER:
Name JOHN FARMER
Address Mac Donald Lane Prineville 97754

(2) TYPE OF WORK (check):
New Well ☐ Deepening ☐ Reconditioning ☒ Abandon ☐
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:
Rotary ☐ Driven ☐
Cable ☒ Jetted ☐
Dug ☐ Bored ☐

(4) PROPOSED USE (check):
Domestic ☒ Industrial ☐ Municipal ☐
Irrigation ☐ Test Well ☐ Other ☐

CASING INSTALLED: Threaded ☐ Welded ☒
6" Diam. from 0 ft. to 58 ft. Gage .250
..." Diam. from ... ft. to ... ft. Gage ...
..." Diam. from ... ft. to ... ft. Gage ...

PERFORATIONS: Perforated? ☒ Yes ☐ No.
Type of perforator used Torch
Size of perforations 1/8 in. by 6 in.
60 perforations from 45 ft. to 57 ft.
... perforations from ... ft. to ... ft.
... perforations from ... ft. to ... ft.

(7) SCREENS: Well screen installed? ☐ Yes ☒ No
Manufacturer's Name ...
Type ... Model No. ...
Diam. ... Slot size ... Set from ... ft. to ... ft.
Diam. ... Slot size ... Set from ... ft. to ... ft.

(8) WELL TESTS: Drawdown is amount water level is lowered below static level
Was a pump test made? ☐ Yes ☒ No If yes, by whom?
Yield: gal./min. with ft. drawdown after hrs.
" " " "
" approx " " "
Bailer test 15 gal./min. with 0 ft. drawdown after 1 hrs.
Artesian flow g.p.m.
Temperature of water 58° Depth artesian flow encountered ... ft.

(9) CONSTRUCTION:
Well seal—Material used Neat Cement
Well sealed from land surface to 18 ft.
Diameter of well bore to bottom of seal 12 in.
Diameter of well bore below seal 8 in.
Number of sacks of cement used in well seal — sacks
Number of sacks of bentonite used in well seal — sacks
Brand name of bentonite —
Number of pounds of bentonite per 100 gallons of water — lbs./100 gals.
Was a drive shoe used? ☐ Yes ☒ No Plugs ... Size: location ... ft.
Did any strata contain unusable water? ☐ Yes ☒ No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? ☐ Yes ☒ No Size of gravel: ...
Gravel placed from ... ft. to ... ft.

(10) LOCATION OF WELL:
County Crook Driller's well number
¼ ¼ Section 30 T. 14S R. 16E W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.
Depth at which water was first found 41 ft.
Static level 37 ft. below land surface. Date 5/30/76
Artesian pressure lbs. per square inch. Date

(12) WELL LOG: Diameter of well below casing —
Depth drilled 58 ft. Depth of completed well 58 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. *Report each change in position of Static Water Level and indicate principal water-bearing strata.*

MATERIAL	From	To	SWL
Brown Sand	45	58	37
repaired well Drilled By Tom Beckner			
Pulled ~~[illegible]~~ unsealed 8" Casing from well			
Pulled 6" O.D 10 gage Pipe with 4" Plastic liner from well.			
replaced with 6" I.D 250 wall well Casing and sealed			

Work started 5/29 1976 Completed 5/30 1976
Date well drilling machine moved off of well 6/3 1976

Drilling Machine Operator's Certification:
This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge ~~and~~ belief.
[Signed] Ron Scanlon (Drilling Machine Operator) Date 6/3, 1976
Drilling Machine Operator's License No. 348

Water Well Contractor's Certification:
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name RON SCANLON WELL DRILLING (Person, firm or corporation) (Type or print)
Address 721 W 2nd St. Prineville 97754
[Signed] Ron Scanlon (Water Well Contractor)
Contractor's License No. 540 Date 6/3, 1976

(USE ADDITIONAL SHEETS IF NECESSARY)

SP*45656-119