NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the

WATER RESOURCES DEPARTMENT,
SALEM, OREGON 97310
within 30 days from the date of well completion.

WATER WELL REPORT
STATE OF OREGON
(Please type or print)
(Do not write above this line)

RECEIVED AUG 22 1978 WATER RES. DEPT. SALEM, OREGON

CROO 1453

State Well No. 14S/16E-30dd

State Permit No.

(1) OWNER:
Name Hudspeth's Sawmill
Address McKay Rd
Prineville 97754

(2) TYPE OF WORK (check):
New Well ☒ Deepening ☐ Reconditioning ☐ Abandon ☐
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:
Rotary ☒ Driven ☐
Cable ☐ Jetted ☐
Dug ☐ Bored ☐

(4) PROPOSED USE (check):
Domestic ☐ Industrial ☐ Municipal ☐
Irrigation ☒ Test Well ☐ Other ☐

CASING INSTALLED: Threaded ☐ Welded ☒
10" Diam. from 0 ft. to 180 ft. Gage .250
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

PERFORATIONS: Perforated? ☒ Yes ☐ No.
Type of perforator used Cutting torch
Size of perforations 1/8 in. by 8 in.
50 perforations from 175 ft. to 180 ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS: Well screen installed? ☐ Yes ☒ No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS: Drawdown is amount water level is lowered below static level
Was a pump test made? ☐ Yes ☐ No If yes, by whom?
d: gal./min. with ft. drawdown after hrs.
" " "
" " "
AIR Bailer test 600 gal./min. with 75 ft. drawdown after hrs.
rtesian flow g.p.m.
perature of water Depth artesian flow encountered ft.

(9) CONSTRUCTION:
Well seal—Material used Cement
Well sealed from land surface to 65 ft.
Diameter of well bore to bottom of seal 14 in.
Diameter of well bore below seal 10 in.
Number of sacks of cement used in well seal sacks
How was cement grout placed?
Was a drive shoe used? ☒ Yes ☐ No Plugs Size: location ft.
Did any strata contain unusable water? ☐ Yes ☒ No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? ☐ Yes ☒ No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:
County Crook Driller's well number 105
NE ¼ SE ¼ Section 30 T. 14S R. 16E W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.
Depth at which water was first found 235 ft.
Static level ft. below land surface. Date
Artesian pressure lbs. per square inch. Date

(12) WELL LOG: Diameter of well below casing 10
Depth drilled 254 ft. Depth of completed well 240 ft.
Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
Bark Dust & Rocks	0	1/2	
Clay & Sand Brown	1/2	6	
Sand & Gravel	6	30	
Sand - Dark Grey (fine)	30	32	
Sandy Clay - Dark Grey	32	60	
Clay - Grey	60	180	
Claystone - Green	180	230	
Pea Gravel	230	254	
Water Bearing			

Work started 8-16 1978 Completed 8-21 1978
Date well drilling machine moved off of well 8-21 1978

Drilling Machine Operator's Certification:
This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] Rodney C. Eller (Drilling Machine Operator) Date 8-21, 1978
Drilling Machine Operator's License No. 1075

Water Well Contractor's Certification:
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name Rod's Well Drilling (Person, firm or corporation) (Type or print)
Address PO Box 351 - Prineville
[Signed] Rodney C. Eller (Water Well Contractor)
Contractor's License No. 663 Date 8-21, 1978

(USE ADDITIONAL SHEETS IF NECESSARY)

SP*45656-119