STATE ENGINEER CROO Well Record  MAILING	STATE WELL NO14/16-31G(2) COUNTYCrookAPPLICATION NO
OWNER: Hudspeth Pine Co. Inc. ADDRESS:	
LOCATION OF WELL: Owner's No STATE:	
Bearing and distance from section or subdivision	
corner	
Altitude at well 2.940+	
TYPE OF WELL: Drilled Date Constructed 1948	
Depth drilled 400 Depth cased 315.5	
	Section
CASING RECORD:  8 inch	
FINISH:	5
AQUIFERS: Sand from 150 to 170 Gravel from 284 to 295	
WATER LEVEL: 50 feet below land surface on March 31, 1948 57.68 feet below land surface on April 15, 1954	
PUMPING EQUIPMENT: TypeTurbine Capacity525G.P.M.	H.P.
WELL TESTS:	
Drawdown ft. after hours	
Drawdown ft. after hours	G.P.M.
USE OF WATER Industrial Temp. °F. SOURCE OF INFORMATION USGS DRILLER or DIGGER ADDITIONAL DATA:	
LogX Water Level Measurements Chemical Analys	is Aquifer Test

## STATE ENGINEER Salem, Oregon

State Well No.	14/16-31G(2)
County	Crook
Application No.	

## Well Log

Owner: Hudspeth Pine Co., Inc.	Owner's No			
Driller: A. M. Jannsen	Date Drill	ed1948		
CHARACTER OF MATERIAL	(Feet below land surface) From To		Thickness (feet)	
luviolacustrine deposits:	· · ·			
Sand and clay	0	170	170	
Clay	170	284	114	
Gravel	284	295	11	
larno (?) formation:				
Clay	295	320	25	
Shale, hard	320	355	35	
Shale, blue-green	355	400	45	
Casing: 8-inch to 315½ feet; perforated from  150 to 170 feet and 285 to 295 feet				
	-			
			·	