NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

CROOK 1573

WATER WELL REPORT
STATE OF OREGON
(Please type or print)
(Do not write above this line)

RECEIVED MAR 6 1975 STATE ENGINEER SALEM, OREGON

State Well No. 14S/16E-32
State Permit No.

(1) OWNER:
Name Coin Mill Works
Address McKay Rd Prineville Oregon 97754

(2) TYPE OF WORK (check):
New Well ☒ Deepening ☐ Reconditioning ☐ Abandon ☐
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:
Rotary ☐ Driven ☐
Cable ☒ Jetted ☐
Dug ☐ Bored ☐

(4) PROPOSED USE (check):
Domestic ☐ Industrial ☒ Municipal ☐
Irrigation ☐ Test Well ☐ Other ☐

(5) CASING INSTALLED: Threaded ☐ Welded ☒
10" Diam. from +1 ft. to 245 ft. Gage 1/4
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

(6) PERFORATIONS: Perforated? ☐ Yes ☒ No.
Type of perforator used
Size of perforations in. by in.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS: Well screen installed? ☐ Yes ☒ No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS: Drawdown is amount water level is lowered below static level
Was a pump test made? ☐ Yes ☒ No If yes, by whom?
Yield: gal./min. with ft. drawdown after hrs.
" " " "
" 60 " no apparent "
Bailer test 1 gal./min. with 1 ft. drawdown after 3 hrs.
Artesian flow g.p.m.
Temperature of water 58 Depth artesian flow encountered — ft.

(9) CONSTRUCTION:
Well seal—Material used Bentonite
Well sealed from land surface to 30 ft.
Diameter of well bore to bottom of seal 14 in.
Diameter of well bore below seal 10 in.
Number of sacks of cement used in well seal — sacks
Number of sacks of bentonite used in well seal 8 sacks
Brand name of bentonite Central Oregon
Number of pounds of bentonite per 100 gallons of water — lbs./100 gals.
Was a drive shoe used? ☒ Yes ☐ ~~No Plugs~~ — Size: location — ft.
Did any strata contain unusable water? ☒ Yes ☒ No
Type of water? Sandy depth of strata 72 - 78
Method of sealing strata off Drill & Drive
Was well gravel packed? ☒ Yes ☐ No Size of gravel: 1-inch
Gravel placed from 240 ft. to 248 ft.

(10) LOCATION OF WELL:
County Crook Driller's well number
¼ ¼ Section 32 T. 14S R. 16E W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.
Depth at which water was first found 72 ft.
Static level 98 ft. below land surface. Date 11-7-74
Artesian pressure — lbs. per square inch. Date

(12) WELL LOG: Diameter of well below casing —
Depth drilled 248 ft. Depth of completed well 248 ft.
Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. *Report each change in position of Static Water Level and indicate principal water-bearing strata.*

MATERIAL	From	To	SWL
Top Soil	0	6	
Brown Clay & Sand	6	78	
Grey Clay	78	140	98
Blue Silt	140	223	
Green Clay Stone	223	240	
Green Gravel & Course Sand	240	248	
Drill & Drive with Bentonite from 30 feet			

Work started 10-20 1974 Completed 11-7 1974
Date well drilling machine moved off of well 11-7 1974

Drilling Machine Operator's Certification:
This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] Dick Akins (Drilling Machine Operator) Date 11-21, 1974
Drilling Machine Operator's License No. 249 & Mac 876

Water Well Contractor's Certification: Lettridge
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name Akins Well Drilling (Person, firm or corporation) (Type or print)
Address P.O. Box 264 Prineville Oregon
[Signed] Dick Akins (Water Well Contractor)
Contractor's License No. 260 Date 11-21, 1974

(USE ADDITIONAL SHEETS IF NECESSARY)

SP*45656-119