

NOTICE TO WATER WELL CONTRACTOR
The original and first copy
of this report are to be
filed with the

RECEIVED
WATER WELL REPORT
STATE ENGINEER
SALEM, OREGON

APR 18 1973
STATE OF OREGON
JAN 10 1973

STATE ENGINEER, SALEM, OREGON
within 30 days from the date
of well completion.

STATE ENGINEER (Please type or print)
SALEM, OREGON
State Well No. 45/17E-33
State Permit No. CROO 1668

(1) OWNER:
Name Clint Cutting
Address 605 Willowsdale Prineville, Ore

(2) TYPE OF WORK (check):
New Well Deepening Reconditioning Abandon
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL: (4) PROPOSED USE (check):
Rotary Driven Domestic Industrial Municipal
Cable Jetted Irrigation Test Well Other
Dug Bored

(5) CASING INSTALLED:
6" Diam. from 0 ft. to 142 ft. Gage 250
" Diam. from " ft. to " ft. Gage
" Diam. from " ft. to " ft. Gage

(6) PERFORATIONS:
Type of perforator used cutting Perforated? Yes No.
Size of perforations in. by in.
perforations from " ft. to " ft.
perforations from " ft. to " ft.
perforations from " ft. to " ft.

(7) SCREENS:
Well screen installed? Yes No
Manufacturer's Name W.P. Model No. W.P.
Type W.P. Diam. Slot size Set from " ft. to " ft.
Diam. Slot size Set from " ft. to " ft.

(8) WELL TESTS:
Drawdown is amount water level is lowered below static level
Was a pump test made? Yes No If yes, by whom?
Yield: gal./min. with ft. drawdown after hrs.
" " " " " "
" " " " " "
Bailer test 10 gal./min. with 200 ft. drawdown after 3 hrs.
Artesian flow now g.p.m.
Temperature of water Depth artesian flow encountered " ft.

(9) CONSTRUCTION:
Well seal—Material used Bentonite
Well sealed from land surface to 20 ft.
Diameter of well bore to bottom of seal 9 in.
Diameter of well bore below seal 6 in.
Number of sacks of cement used in well seal now sacks
Number of sacks of bentonite used in well seal 2 sacks
Brand name of bentonite Central Oregon Bentonite
Number of pounds of bentonite per 100 gallons of water 200 lbs./100 gals.
Was a drive shoe used? Yes No Plugs no Size: location " ft.
Did any strata contain unusable water? Yes No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? Yes No Size of gravel: " ft.
Gravel placed from " ft. to " ft.

(10) LOCATION OF WELL:
County Crook Driller's well number 230
1/4 1/4 Section 33 T. 77S R. 17E W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.
Depth at which water was first found 300 ft.
Static level 90 ft. below land surface. Date 12/10/72
Artesian pressure now lbs. per square inch. Date

(12) WELL LOG: Diameter of well below casing 6"
Depth drilled 345 ft. Depth of completed well 345 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
clay yellow	0	12	
brown clay	12	35	
broken rock & clay	35	90	
rock (hard)	90	110	
broken rock	110	140	
rock (hard)	140	200	
broken rock & clay	200	250	
blue clay	250	300	
broken rock (water bearing)	300	305	90
red clay	305	310	90
blue clay	310	345	90

Work started 11/18 1972 Completed 12/10 1972
Date well drilling machine moved off of well 12/10 1972

Drilling Machine Operator's Certification:
This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] Archie Fox Date 12/10, 1972
(Drilling Machine Operator)
Drilling Machine Operator's License No. 389

Water Well Contractor's Certification:
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name Archie Fox, Well Drilling
(Person, firm or corporation) (Type or print)
Address Rt. 1 Box 149 Prineville, Ore
[Signed] Archie Fox
(Water Well Contractor)
Contractor's License No. 444 Date 12/22, 1972