NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the
STATE ENGINEER, SALEM, OREGON 97310
within 30 days from the date of well completion.

CROO 1679

WATER WELL REPORT
STATE OF OREGON
(Please type or print)
(Do not write above this line)

RECEIVED
FEB 01977
WATER RESOURCES DEPT.
SALEM, OREGON

State Well No. 14S/17E-33 1
State Permit No.

(1) OWNER:
Name Ed Grant - Harold Orr (Lakeshore Motel Park)
Address MSR Box 108 Prineville, Ore 97754

(2) TYPE OF WORK (check):
New Well ☒ Deepening ☐ Reconditioning ☐ Abandon ☐
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:
Rotary ☐ Driven ☐
Cable ☒ Jetted ☐
Dug ☐ Bored ☐

(4) PROPOSED USE (check):
Domestic ☒ Industrial ☐ Municipal ☒
Irrigation ☐ Test Well ☐ Other ☐

CASING INSTALLED: Threaded ☐ Welded ☒
6" Diam. from 0+2 ft. to 70 ft. Gage .250
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

PERFORATIONS: Perforated? ☒ Yes ☐ No.
Type of perforator used Cutting Torch
Size of perforations 1/4 in. by 6 in.
64 perforations from 50 ft. to 70 ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS: Well screen installed? ☐ Yes ☒ No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS: Drawdown is amount water level is lowered below static level
Was a pump test made? ☒ Yes ☐ No If yes, by whom?
Yield: 30 gal./min. with 2 ft. drawdown after 24 hrs.
" " " "
" " " "
Bailer test gal./min. with ft. drawdown after hrs.
Artesian flow g.p.m.
Temperature of water Depth artesian flow encountered ft.

(9) CONSTRUCTION:
Well seal—Material used Cement
Well sealed from land surface to 20 pressure grouted ft.
Diameter of well bore to bottom of seal 10 in.
Diameter of well bore below seal 6 in.
Number of sacks of cement used in well seal 18 sacks
Number of sacks of bentonite used in well seal sacks
Brand name of bentonite
Number of pounds of bentonite per 100 gallons of water lbs./100 gals.
Was a drive shoe used? ☐ Yes ☒ No Plugs Size: location ft.
Did any strata contain unusable water? ☐ Yes ☒ No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? ☐ Yes ☒ No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:
County Crook Driller's well number
NW ¼ SE ¼ Section 33 T. 14S R. 17E W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.
Depth at which water was first found 55 ft.
Static level 29 ft. below land surface. Date 12/20/76
Artesian pressure none lbs. per square inch. Date

(12) WELL LOG: Diameter of well below casing 6
Depth drilled 70 ft. Depth of completed well 70 ft.
Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. *Report each change in position of Static Water Level and indicate principal water-bearing strata.*

MATERIAL	From	To	SWL
Gravel & Sand Brown	0	1	
Clay & Rock Brown	1	15	
Clay Brown	15	41	
Clay & Boulder Brown	41	55	
Gravel & Clay Brown (water bearing)	55	70	29

Work started 12-18 1976 Completed 12-20 1976
Date well drilling machine moved off of well 12-20 1976

Drilling Machine Operator's Certification:
This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] Rodney C. Eden (Drilling Machine Operator) Date 1/10, 1977
Drilling Machine Operator's License No. 1075

Water Well Contractor's Certification:
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name Archie Fox, Well Drilling (Person, firm or corporation) (Type or print)
Address Rt. 3 Box 202 Prineville, Ore 97754
[Signed] Archie Fox (Water Well Contractor)
Contractor's License No. 444 Date 1/10, 1977

(USE ADDITIONAL SHEETS IF NECESSARY)

SP*45656-119